




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : G01N 33/543, 27/327, C12Q 1/28, 1/58, 1/68		A1	(11) International Publication Number: WO 00/11473
			(43) International Publication Date: 2 March 2000 (02.03.00)
(21) International Application Number: PCT/GB99/02785 (22) International Filing Date: 24 August 1999 (24.08.99) (30) Priority Data: 98116346 24 August 1998 (24.08.98) RU (71) Applicant (for all designated States except US): SEN- SOR-TECH LIMITED [-/-]; Don Road, P.O. Box 301, St. Helier, Jersey JE4 8UG (GB). (71) Applicant (for LR only): BALDOCK, Sharon, Claire [GB/GB]; 27 Furnival Street, London EC4A 1PQ (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): FARMAKOVSKI, Dmitri Alexandrovich [RU/RU]; Building 48, Flat 46, Kastanaevskaya Street, Moscow, 1121108 (RU). MI- LANOVSKI, Yevgeni Yurevich [RU/RU]; Building 48, Flat 46, Kastanaevskaya Street, Moscow, 1121108 (RU). CHERKASOV, Vladimir Rurikovich [RU/RU]; Building 48, Flat 46, Kastanaevskaya Street, Moscow, 1121108 (RU). BIRYUKOV, Yuri Sergeyevich [RU/RU]; Building 48, Flat 46, Kastanaevskaya Street, Moscow, 1121108 (RU). LEONARDOVA, Olga [RU/CA]; 1830-11 Avenue S.W. #401, Calgary, Alberta T3C 0N6 (CA).		(74) Agent: BOULT WADE TENNANT; 27 Furnival Street, London EC4A 1PQ (GB). (81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report.	

(54) Title: METHOD OF ELECTROCHEMICAL ANALYSIS OF AN ANALYTE

(57) Abstract

A sensing electrode for use in methods of electrochemical analysis comprising an electrically conducting electrode coated with an electroconductive polymer membrane having immobilised therein or adsorbed thereto adaptor molecules avidin, streptavidin, anti-fit antibodies through which the sensing electrode can be made specific for an analyte under test by the binding of receptors specific for the analyte.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

METHOD OF ELECTROCHEMICAL ANALYSIS
OF AN ANALYTE

The invention relates to methods of
5 electrochemical detection of analytes and to sensing
electrodes for use in methods of electrochemical
detection.

Electrochemical analysis of analytes, such as
various antigens, antibodies, DNA molecules etc, in
10 biological fluids using biosensors is one of the most
promising and attractive methods of instrument
analysis. The sustained interest and large number of
publications in this field are explained by a number
of basic advantages of the method, namely high
15 sensitivity, simplicity and the use of relatively
simple and inexpensive equipment.

It is known in the art to construct biosensor
devices based on the use of electroconductive polymer
films, such as polypyrrole or polythiophene, which
20 transduce a chemical signal associated with the
presence of an analyte into a measurable electrical
signal (see [1] and [2]).

EP-A-0 193 154 describes an electrode for use in
electrochemical detection, the electrode being coated
25 with a polypyrrole or polythiophene film.
Bioreceptors complementary to the analyte to be tested
are adsorbed onto the surface of the electroconductive
polymer film after polymerisation. WO 89/11649
describes an alternative process for the production of
30 polymeric electrodes for use in electrochemical
assays. In this process bioreceptor molecules having
the desired binding specificity are incorporated into
a film of electroconductive polymer during
polymerisation. Using the processes described in EP-
35 A-0 193 154 and WO 89/11649 for each given assay it is

- 2 -

necessary to synthesise a different sensing electrode having immobilized bioreceptors capable of specifically binding to the analyte for which one wants to test.

5 The applicants' published application PCT/GB98/00548 describes a potentiometric method of electrochemical analysis using an electrochemical sensing electrode comprising a metallic potentiometric electrode again coated with a layer of
10 electroconductive polymer containing immobilised bioreceptor molecules which bind specifically to the analyte under test. The presence of analyte is indicated by a change in surface charge of the sensing electrode upon binding of analyte to the immobilised
15 bioreceptors. The analyte detection procedure is carried out by first assembling an electrochemical cell comprising the sensing electrode and a reference electrode connected together by means of a measuring device immersed in a working buffer solution of fixed
20 pH. A base value of potential difference between the sensing electrode and the reference electrode is recorded, the sensing and reference electrodes are then brought into contact with a solution of higher ionic strength suspected of containing the analyte but
25 with pH the same as the working buffer and potential difference is again recorded. The sensing and reference electrodes are finally transferred to clean working buffer and potential is again recorded. The change in potential difference between the sensing
30 electrode and the reference electrode resulting from a change in ionic strength of the buffer at constant pH in the presence of analyte is proportional to the concentration of analyte.

35 As shown in references [13, 14, 15, 16] and in [3], the response (amount and rate of potential

- 3 -

change) of the sensing electrode with polymer film containing bioreceptors to a step-change in ionic strength of the ambient solution (so-called "ion-step" procedure) is to a large extent determined by the charge on the polymer film. Apart from the material from which it is made, the polymer film charge is determined by the charge of the receptor molecules bound in it. If the receptor charge changes as a result of an affinity reaction with a specific analyte, the response of the sensing electrode will also change as a result of the ion-step procedure carried out after contact between the sensing electrode and the test fluid. It should be noted that, because of the amphoteric nature of the majority of analytes, the receptor charge depends on the pH of the solution and it is therefore very important to maintain a constant pH of the solution during the ion-step procedure.

Thus, in the previously described methods, based on measurement of the change in response of the sensing electrode to the ion-step procedure carried out before and after contact between the sensing electrode and test fluid, it is possible to make a determination as to the presence in the test fluid of analyte specific to the receptors bound on the sensing electrode. In the ideal case, the variation in the charge of the receptors in the membrane and, hence, the change in the sensing electrode response is directly proportional to the concentration in the test fluid of analyte specific to the receptors bound on the sensing electrode. However, in real conditions, the charge of the same analyte can vary considerably, which produces inconsistent quantitative results. Moreover, the affinity reactions are not always accompanied by a change in receptor charge. This

- 4 -

normally occurs when testing small or non-charged antigens [14].

5 In summary, the shortcomings of the prior art methods of electrochemical detection based on the use of electroconductive polymer electrodes include complexity and limited amenability to industrialisation of the sensing electrode manufacturing process, inconsistency of the characteristics of the sensing electrodes obtained,
10 limited ability to store the sensing electrodes without loss of performance. In addition, the previously described protocols for electrochemical detection, particularly the method described in PCT/GB98/00548, are of limited use for the detection
15 of small and non charged molecules or molecules whose isoelectric point is close to the isoelectric point of the receptors immobilised on the surface of the sensing electrode.

20 The present invention provides a method of electrochemical analysis of an analyte in a sample which is to a large extent free of the shortcomings inherent in the methods described above in that it widens the scope of application by virtue of the ability to analyse small and non-charged molecules,
25 provides strictly quantitative results, makes the electrode manufacturing process more amenable to industrial production methods, increases the productivity of the analysis, improves reproducibility and therefore enhances reliability of the results
30 obtained.

Thus, in a first aspect the invention provides a sensing electrode for use in methods of electrochemical detection of an analyte, the sensing electrode comprising an electrically conductive
35 electrode coated with an electroconductive polymer

- 5 -

with adaptor molecules selected from the group consisting of avidin, streptavidin, anti-FITC antibodies and a molecule capable of binding to at least one class of receptor molecules immobilised therein or adsorbed thereto.

One of the principal problems inherent in electrochemical analysis methods using sensing electrodes is the problem of retention over time of the native properties of the receptors fixed on the sensing electrodes. Relative progress has been achieved in this field only for a limited number of enzyme sensing electrodes [7]. For the majority of electrochemical sensing electrodes using refined receptors known in the literature [8, 9, 10], their useful storage life is simply not stated. The retention of the native properties of immobilised receptors is particularly critical where antibodies are used as the receptors, which is attributable to their inherent high degree of conformational variability.

In contrast, it is known that antibodies and other biomolecules retain their useful properties over very long periods of time when stored in the form of concentrated solutions; therefore the problem of prolonged storage of the sensing electrodes without loss of working characteristics may be overcome by rapid immobilisation of receptors before use or even during the electrochemical detection procedure.

This problem is solved in the declared invention by use of so-called adaptor molecules which are immobilized in or adsorbed to the electroconductive polymer. The purpose of the adaptor molecules is to link receptor molecules specific to the analyte under test to the surface of the sensing electrode. As will be discussed below, with the use

- 6 -

of adaptor molecules it is possible to temporally
separate steps in the production of the sensing
electrodes. Thus, it is feasible to manufacture the
electrodes with immobilised/adsorbed adaptor
5 molecules, store them for an extended period of time
and then fix the specific receptors onto the electrode
either before or during the electrochemical analysis.
With the selection of appropriate adaptor molecules it
is also possible to manufacture 'universal' sensing
10 electrodes containing adaptor molecules capable of
binding to a whole range of different receptor
molecules. Specificity for the analyte under test is
conferred on the 'universal' sensing electrode simply
by binding to the adaptor molecules receptors of the
15 appropriate specificity. It is therefore no longer
necessary to incorporate receptors of the desired
specificity during the electrodeposition process.

The proteins avidin and streptavidin are
preferred for use as adaptor molecules. Avidin, a
20 protein obtained from raw eggs, consists of four
identical peptide sub-units, each of which has one
site capable of bonding with a molecule of the co-
factor biotin. Biotin (vitamin H) is an enzyme co-
factor present in very minute amounts in every living
25 cell and is found mainly bound to proteins or
polypeptides. The ability of biotin molecules to
enter into a binding reaction with molecules of avidin
or streptavidin (a form of avidin isolated from
certain bacterial cultures, for example *Streptomyces*
30 *avia*) and to form virtually non-dissociating
"biotin-avidin" complexes during this reaction
(dissociation constant $\sim 10^{-15}$ Mol/l) is well known
[11, 12].

Investigations carried out by the authors of the
35 declared invention have shown that avidin and

- 7 -

streptavidin immobilised in an electroconductive polymer film, retain their native properties for an extended period of time (at least one year and possibly longer) and can be used throughout this period to link with biotin conjugated receptors. Techniques which allow the conjugation of biotin to a wide range of different molecules are well known in the art. Thus sensing electrodes with immobilised avidin or streptavidin can easily be made specific for a given analyte merely by binding of the appropriate biotinylated receptors.

Although avidin and streptavidin are the preferred adaptor molecules it is within the scope of the invention to use alternative adaptor molecules, in particular molecules capable of specifically binding to at least one class of receptor molecules. Included within this group of alternative adaptor molecules are protein A, protein G and lectins. These molecules all share the ability to bind to at least one class of receptor molecules, by which is meant that they are able to specifically bind to a common binding site motif which is present in each member of a group of receptor molecules, the dissociation constant for the binding interaction being less than 10^{-8} Mol/l. By way of example, protein A (a 42kD polypeptide isolated from *Staphylococcus aureus* or obtained by recombinant DNA technology) binds to immunoglobulins, particularly IgG, from a wide range of mammalian species at the Fc region; and protein G (IgG Fc receptor Type III, see Bjorck, L. and Kronvall, G., J. Immunol., 133, 969 (1984)) also binds to the Fc region of IgG molecules from a wide range of mammalian species. Lectins are proteins which bind to sugar moieties which may be present on glycoproteins or carbohydrates. Each type of lectin has specificity for a given sugar moiety and

- 8 -

thus will be able to bind a range of glycoproteins or complex carbohydrates carrying the correct sugar moiety.

5 In a still further embodiment anti-FITC antibodies can be used as the adaptor molecules. In this embodiment, the specificity of the sensing electrode for analyte can be conferred by binding to the anti-FITC antibodies FITC labelled receptors of the appropriate specificity.

10 The use of adaptor molecules in/on the electroconductive polymer film also considerably improves the reliability of the results obtained during electrochemical analysis by reducing non-specific interactions of the components of the test
15 solution during contact with the sensing electrode, which is linked to the blocking of the free surface of the electroconductive polymer by adaptor molecules. The use of adaptor molecules also increases the technical efficiency of the sensing electrode
20 manufacturing process, for example by eliminating the need for an additional surface blocking procedure.

The potentiometric sensing electrodes of the invention are inexpensive to manufacture and so for convenience can be produced in a disposable format,
25 intended to be used for a single electrochemical detection experiment or a series of detection experiments and then thrown away. The invention further provides an electrode assembly including both a sensing electrode and a reference electrode required
30 for electrochemical detection. As will be discussed below, suitable reference electrodes include silver/silver chloride and calomel electrodes. Conveniently, the electrode assembly could be provided as a disposable unit comprising a housing or holder
35 manufactured from an inexpensive material equipped

with electrical contacts for connection of the sensing electrode and reference electrode.

The sensing electrodes of the invention can be used in a wide range of electrochemical analysis procedures, including (but not limited to) double antibody sandwich assays for antigens, double antigen sandwich assays for antibodies, competitive assays for antigens, competitive assays for antibodies, serological assays for the determination of human antibodies (e.g. Rubella IgG antibodies using labelled antihuman antibodies) and IgM assays (e.g. IgM-Rubella antibodies).

In a second aspect the invention provides a method of producing a sensing electrode for use in methods of electrochemical detection of an analyte, the sensing electrode comprising an electrically conductive electrode coated with an electroconductive polymer with adaptor molecules selected from the group consisting of avidin, streptavidin and a molecule capable of binding to at least one class of receptor molecules immobilized therein, the method comprising the steps of:

- (a) preparing an electrochemical polymerisation solution comprising monomeric units of the electroconductive polymer and adaptor molecules,
- (b) immersing the electrode to be coated in the electrochemical polymerisation solution, and
- (c) applying a cyclic electric potential between the electrode and the electrochemical polymerisation solution to coat the electrode by electrochemical synthesis of the polymer from the solution, said cyclic electric potential being applied for at least one full cycle.

The invention further provides a method of producing a sensing electrode for use in methods of

- 10 -

electrochemical detection of an analyte in a sample, the electrode comprising an electrically conductive electrode coated with an electroconductive polymer with adaptor molecules selected from the group
5 consisting of avidin, streptavidin and a molecule capable of binding to at least one class of receptor molecules adsorbed thereto, the method comprising steps of:

(a) preparing an electrochemical polymerisation
10 solution comprising monomeric units of the electroconductive polymer,

(b) immersing the electrode to be coated in the electrochemical polymerisation solution,

(c) applying a cyclic electric potential
15 between the electrode and the electrochemical polymerisation solution to coat the electrode by electrochemical synthesis of the polymer from the solution, said cyclic electric potential being applied for at least one full cycle; and

(d) contacting the coated electrode with a
20 solution comprising adaptor molecules such that the adaptor molecules are adsorbed onto the electroconductive polymer coating of the electrode.

According to the methods of the invention a film
25 of electroconductive polymer is deposited onto the surface of an electrically conductive electrode by electrochemical synthesis from a monomer solution. The electrically conductive electrode is preferably a standard potentiometric electrode possessing metallic
30 or quasi-metallic conductivity which is stable in aqueous media. As will be illustrated in the examples included herein, electrodeposition of the electroconductive polymer film is carried out using a solution containing monomers, a polar solvent and a
35 background electrolyte. Pyrrole, thiophene, furan or

- 11 -

aniline are the preferred monomers. Deionised water is preferably used as the polar solvent.

As is well known to persons skilled in the art, electroconductive polymers are often doped at the electrochemical synthesis stage in order to modify the structure and/or conduction properties of the polymer. A typical dopant anion is sulphate (SO_4^{2-}) which is incorporated during the polymerisation process, neutralising the positive charge on the polymer backbone. Sulphate is not readily released by ion exchange and thus helps to maintain the structure of the polymer. In the present invention it is preferred to use dopant anions having maximum capability for ion exchange with the solution surrounding the polymer in order to increase the sensitivity of the electrodes. This is accomplished by using a salt whose anions have a large ionic radius as the background electrolyte when preparing the electrochemical polymerisation solution. Suitable salts whose anions have large ionic radius include sodium dodecyl sulphate and dextran sulphate. The concentration of these salts in the electrochemical polymerisation solution is varied according to the type of test within the range 0.005 - 0.05 M.

As reported in a number of papers [4, 5], the ease with which ion exchange takes place and the rapidity with which ion equilibrium is attained for electroconductive polymers immersed in a solution are essentially dependent on the size of the anti-ion introduced at the electrodeposition stage: the larger the ionic radius of the anti-ion, the more readily ion-exchange reactions take place and the more rapidly a state of equilibrium is reached. This is directly linked to the value and rate of change of

- 12 -

the potential of the "metal electrode -
electroconductive polymer" system in response to
variation in the ion composition of the solution [6].

5 The electroconductive polymer membrane performs
a dual function, serving both to bind the receptor to
the surface of the sensing electrode, and to render
the sensing electrode sensitive to variations in the
composition of the buffer solution. In particular,
changes in the composition of the buffer solution
10 which affect the redox composition of the
electroconductive polymer result in a corresponding
change in the steady state potential of the sensing
electrode.

Adaptor molecules may either be immobilized in
15 the electroconductive polymer film at the
electrochemical synthesis stage by adding adaptor
molecules to the electrochemical polymerisation
solution or may be adsorbed onto the surface of the
electroconductive polymer film after electrochemical
20 polymerisation. In the former case, a solution of
adaptor molecules may be added to the
electrodeposition solution immediately before the
deposition process. The deposition process works
optimally if the storage time of the finished
25 solution does not exceed 30 minutes. Depending on
the particular type of test, the concentration of
adaptor molecules in the solution may be varied in
the range 5.00 - 100.00 $\mu\text{g/ml}$. Procedures for
electrodeposition of the electroconductive polymer
30 from the solution containing adaptor molecules are
described in the examples included herein. On
completion of electrodeposition process, the sensing
electrode obtained may be rinsed successively with
deionised water and 0.01 M phosphate-saline buffer
35 solution and, depending on the type of test, may then

- 13 -

be placed in a special storage buffer solution containing microbial growth inhibitors or bactericidal agents (e.g gentamicin), or dried in dust-free air at room temperature.

5 Where the adaptor molecules are to be adsorbed after completion of the electrodeposition process the following protocol may be used (although it is hereby stated that the invention is in no way limited to the use of this particular method), the sensing electrode
10 is first rinsed with deionised water and placed in freshly prepared 0.02M carbonate buffer solution, where it is held for 15-60 minutes. The sensing electrode is then placed in contact with freshly-prepared 0.02M carbonate buffer solution containing
15 adaptor molecules at a concentration of 1.00 - 50.00 $\mu\text{g/ml}$, by immersing the sensing electrode in a vessel filled with solution, or by placing a drop of the solution onto the surface of the sensing electrode. The sensing electrode is incubated with the solution
20 of adaptor molecules, typically for 1-24 hours at +4°C. After incubation, the sensing electrode is rinsed with deionised water and placed for 1-4 hours in a 0.1M phosphate-saline buffer solution. Depending on the type of test, the sensing electrode may then
25 be placed either in a special storage buffer solution containing microbial growth inhibitors or bactericidal agents, or dried in dust-free air at room temperature.

 When the adaptor molecules are avidin or
30 streptavidin, the above-described methods of the invention for producing a sensing electrode may optionally comprise a further step of contacting the coated electrode with a solution comprising specific receptors conjugated with biotin such that said
35 biotinylated receptors bind to molecules of avidin or

- 14 -

streptavidin immobilised in or adsorbed to the electroconductive polymer coating of the electrode via a biotin/avidin or biotin/streptavidin binding interaction.

5 Research carried out both by the authors of the declared invention, and by others [12], has shown that the biotinylation of receptors under optimal conditions does not alter their properties (affinity, storage qualities, etc.) compared with their non-
10 biotinylated equivalents.

 Conjugation of biotin with the corresponding receptors, a process known to those skilled in the art as biotinylation, can be carried out using one of the known procedures, for example as described in
15 [12]. In addition, a number of ready-made preparations of biotinylated antibodies of different specificity are commercially available, e.g. Anti-Human IgG or Anti-Human IgA goat biotin-labelled antibodies made by Calbiochem-Novabiochem, USA.

20 One of the significant advantages of using biotinylated receptors is the ability to vary the specificity of the sensing electrode, by producing a reaction between the avidin or streptavidin bound on the sensing electrode and the corresponding
25 biotinylated receptors. As discussed previously, the sensing electrode with bound avidin/streptavidin is in effect a 'universal sensing electrode' and specificity to the desired molecules under test is conferred by the binding of the appropriate
30 biotinylated receptors. To make the sensing electrode with bound avidin or streptavidin specific to the analyte under test, a reaction is carried out between the avidin or streptavidin bound on the
35 sensing electrode with biotinylated receptors, for which purpose the sensing electrode is brought into

- 15 -

contact with a solution of the latter at room temperature, either by immersing the sensing electrode in a vessel filled with solution, or by placing drop of solution on the sensing electrode surface (concentration of biotinylated receptors in the solution is generally 0.1 - 100 $\mu\text{g/ml}$; contact time 3-15 minutes).

The receptor molecules can be any molecule capable of specifically binding to another molecule (an analyte). Suitable types of receptors include monoclonal and polyclonal antibodies, chimaeric antibodies, fragments of antibodies which retain the ability to recognise antigen (e.g. Fab and Fab2 fragments), recombinant proteins and fragments thereof, synthetic peptides, antigens, single-strand DNA, RNA or PNA molecules, hormones, hormone receptors, enzymes, chemical compounds etc.

As discussed above, the electrochemical detection methods known in the art using potentiometric sensing electrodes are of limited use in the detection of small and non-charged antigens. In order to overcome this problem, and to obtain strictly quantitative results, use may be made of secondary receptors or competing molecules conjugated with a charge label.

Accordingly, in a further aspect the invention provides a method of electrochemical detection of an analyte in a sample, which method comprises the steps of:

(a) providing a sensing electrode having an electroconductive polymer coating, the coating having immobilised therein or adsorbed thereto receptors which specifically bind to the desired analyte to be detected in the sample;

(b) treating the sensing electrode by immersion

- 16 -

in a test solution comprising the sample so that said desired analyte binds to said immobilised or adsorbed receptors;

5 (c) contacting the sensing electrode with a solution comprising secondary receptors capable of binding to said analyte at a site spatially distinct from the site of binding to the immobilised or adsorbed receptors, said secondary receptors being conjugated with a charge label;

10 (d) monitoring the electric potential difference between the treated sensing electrode and a reference electrode when both are immersed in an electrolyte; and

15 (e) monitoring the electric potential difference between the sensing electrode and a reference electrode following a change in the ionic strength of the electrolyte at constant pH.

The affinity reaction steps of the above-described method are equivalent to a standard sandwich assay well known to those skilled in the art. The sandwich format of analysis is particularly useful for the detection of polyvalent antigens in which case the receptors and labelled secondary receptors used in the test are antibodies which bind to different, spatially distinct epitopes on the antigen. The sandwich format can also be used where the antigen carries two or more identical epitopes which are spatially separated. In this latter case, the receptors and labelled secondary receptors used in the test may be antibodies of identical specificity.

35 It is also within the scope of the invention to perform the electrochemical analysis in a competitive assay format. Therefore, the invention also provides a method of electrochemical detection of an analyte

- 17 -

in a sample comprising the steps of:

(a) providing a sensing electrode having an electroconductive polymer coating, the coating having immobilised therein or adsorbed thereto receptors which are capable of binding to the desired analyte to be detected in the sample;

(b) treating the sensing electrode by immersion in a test solution comprising the sample so that said desired analyte binds to said immobilised or adsorbed receptors;

(c) contacting the sensing electrode with a solution comprising competing molecules capable of binding to said immobilised or adsorbed receptors, said competing molecules being conjugated with a charge label;

(d) monitoring the electric potential difference between the treated sensing electrode and a reference electrode when immersed in an electrolyte; and

(e) monitoring the electric potential difference between the sensing electrode and a reference electrode following a change in the ionic strength of the electrolyte at constant pH.

In this competitive electrochemical assay the competing molecules could be labelled analyte or labelled structural analogs of the analyte which are capable of binding to the same analyte binding site on the immobilized/adsorbed receptors (see Fig 5B and Fig 7B). The use of labelled analyte as the competing molecule is particularly preferred for the detection of small analyte molecules (e.g. digoxin, as described in the examples included herein). Alternatively, the competing molecule may bind to a different site on the immobilized/adsorbed receptor. For example, if the immobilized receptor is an

antibody, the competing molecule could be an anti-immunoglobulin antibody (preferably Fab-specific) or even an anti-idiotypic antibody of the appropriate specificity (see Fig 5A and Fig 7A).

5 As would be readily understood by persons skilled in the art, with reference to Figures 5A, 5B, 7A and 7B of the present application, the competitive detection methods are usually dependent on their being an excess of receptor sites on the surface of
10 the sensing electrode. Those receptors which do not bind analyte will be available for binding to the competing molecule. Assuming that the total number of receptor sites remains constant, the amount of bound competing molecule will be inversely
15 proportional to the amount of analyte present.

In order to transduce the chemical signal associated with the concentration of the analyte into a measurable electrical signal the charge label which is conjugated to the secondary receptors or competing
20 molecules can be any charge label having the following properties:

- (i) carries a net charge (positive or negative) at the pH of the electrolyte of part (d); and
- (ii) the magnitude of this charge changes in response
25 to a change in the ionic strength of the electrolyte at constant pH.

Preferably the charge label is highly charged, i.e. has a net charge at the pH of the electrolyte of part (d) of greater than one electrostatic unit (e).
30 Suitable charge labels include gold, ferrocene and latex microspheres. The magnitude of the charge on the charge label affects the redox composition of the electroconductive polymer coating on the sensing electrode such that the step change in ionic strength
35 between steps (d) and (e) results in a detectable

change in potential difference between the sensing electrode and the reference electrode. The charge label is only brought into close proximity of the electroconductive polymer on formation of
5 receptor/analyte/secondary receptor complexes (sandwich assay) or receptor/competing molecule complexes (competitive assay). The use of a charge label thus makes it possible to obtain correct qualitative results and considerably extends the
10 spectrum of testable analytes by virtue of the ability to test small and non-charged analytes.

Latex microspheres are the preferred type of charge label conjugated with the secondary receptors or competing molecules. Conjugation with latex
15 microspheres may be carried out using one of the known techniques, for example as described in [17] or [18], or using special commercially available kits for the conjugation of antibodies with latex microspheres, for example "Carbodiimide Kit for
20 Carboxylated Beads" made by Polysciences Inc., USA, following the protocol supplied by the manufacturer. Certain ready-made latex conjugates are commercially available from specialist manufacturers, e.g. Polysciences Inc., USA.

25 As an alternative to the use of a charge label, it is also possible to perform electrochemical detection procedures equivalent to those described above using secondary receptors or competing molecules conjugated with an enzyme labels in order
30 to transduce the chemical signal associated with the concentration of the analyte into a measurable electrical signal.

Accordingly, the invention further provides a method of electrochemical detection of an analyte in
35 a sample, which method comprises the steps of:

- 20 -

(a) providing a sensing electrode having an electroconductive polymer coating, the coating having immobilized therein or adsorbed thereto receptors which are capable of binding to the desired analyte to be detected in the sample;

(b) treating the sensing electrode by immersion in a test solution comprising the sample so that the said analyte binds to said immobilized or adsorbed receptors;

(c) contacting the sensing electrode with a solution comprising secondary receptors capable of binding to said analyte at a site spatially distinct from the site of binding to immobilized or adsorbed receptors, said secondary receptors being conjugated with an enzyme;

(d) monitoring the electric potential difference between the treated sensing electrode and a reference electrode when both are immersed in an electrolyte; and

(e) monitoring the electric potential difference between the sensing electrode and a reference electrode following exposure to an electrolyte comprising the substrate for said enzyme.

Also within the scope of the invention is the corresponding competitive method of electrochemical detection comprising the steps of:

(a) providing a sensing electrode having an electroconductive polymer coating, the coating having immobilized therein or adsorbed thereto receptors which are capable of binding to the desired analyte to be detected in the sample;

(b) treating the sensing electrode by immersion in a test solution comprising the sample so that the said desired analyte binds to said immobilized or adsorbed receptors;

- 21 -

(c) contacting the sensing electrode with a solution comprising competing molecules capable of binding to said immobilized or adsorbed receptors, said competing molecules being conjugated with an enzyme;

d) monitoring the electric potential difference between the treated sensing electrode and a reference electrode when both are immersed in an electrolyte; and

e) monitoring the electric potential difference between the sensing electrode and a reference electrode following exposure to an electrolyte comprising the substrate for said enzyme.

In one embodiment of the above-described methods the enzyme conjugated to the secondary receptors or competing molecules is capable of converting a substrate which directly affects the redox composition of the electroconductive polymer coating of the sensing electrode into a product which has no detectable effect on the redox composition of the electroconductive polymer. An example of such an enzyme is horseradish peroxidase.

In an alternative embodiment, the enzyme conjugated to the secondary receptors or competing molecules is capable of converting a substrate which has no detectable effect on the redox composition of the electrochemical polymer coating of the sensing electrode to a product capable of directly or indirectly affecting the redox composition of the electroconductive polymer. One way in which the product of the enzymic reaction may indirectly affect the redox composition of the electroconductive polymer is by causing a change in the pH of the electrolyte (for this embodiment the pH of the electrolyte is not buffered). An example of an

enzyme which generates such a product is urease.

In a still further embodiment, the enzyme conjugated to the secondary receptors or the competing molecules is capable of converting a product which has no detectable effect on the redox composition of the electroconductive polymer coating of the sensing electrode into a product which is a substrate for a second enzyme, the action of the second enzyme generating a second product which directly or indirectly affects the redox composition of the electroconductive polymer.

In all embodiments the conjugated enzyme is brought into close proximity of the electroconductive polymer by formation of receptor/analyte/secondary receptor complexes (sandwich format) or by formation of receptor/competing molecule complexes (competitive format).

The conjugation of secondary receptors or competing molecules with enzyme labels may be performed by any of the techniques known in the art (see, for example [19]). Use can also be made of widely available commercial preparations of conjugates of receptors of different specificity with different enzyme labels.

All of the above methods of electrochemical detection can be performed using any type of receptor capable of specifically binding to another molecule (an analyte). Suitable types of receptors include monoclonal and polyclonal antibodies, chimaeric antibodies, fragments of antibodies which retain the ability to recognise antigen (e.g. Fab and Fab2 fragments), recombinant proteins and fragments thereof, synthetic peptides, antigens, single-strand DNA, RNA or PNA molecules, hormones, hormone receptors, enzymes, chemical compounds etc.

Regardless of whether the secondary receptors or competing molecules are conjugated with a charge or enzyme label, the maximum degree of specificity and sensitivity for all of the detection methods of the invention is achieved by performing the affinity reactions (i.e. steps (a) to (c)) in a 'sequential' format. This is particularly so when the analyte under test is a polyvalent antigen (i.e. the sandwich assay). In the sequential format the sensing electrode with bound receptors is first brought into contact with a test solution comprising the sample to be tested for the presence of the analyte. As used herein the term 'sample' includes within its scope any material which it is desired to test for the presence of analyte, including biological fluids such as whole blood, serum, plasma, urine, lymph, cerebrospinal fluid or semen, environmental fluids, materials used or produced in the food and drink industry or a dilution or extract of any of the above. The sample may also comprise a solution or extract of a solid material. The container used for the test solution may be the well of a microtiter plate, a micro-centrifuge tube or any other vessel of suitable size. The volume of test solution will generally be 5-200 μ l depending on the geometrical dimensions of the sensing electrode. The contact time between the sensing electrode and test solution is typically 3-30 minutes at 15-40°C with or without continuous mixing.

Following contact with the test solution the sensing electrode is transferred to a vessel containing solution of labelled secondary receptors. The vessel and volume of solution used are similar to those used for contact between the sensing electrode and test solution. The

concentration of labelled secondary receptors or
labelled competing molecules in the solution is
typically 1-100 $\mu\text{g/ml}$ depending on the required
sensitivity of the test. Contact is made for 3-30
5 minutes at 15-40°C with or without continuous mixing.

As an alternative to the 'sequential' format it
is possible to substantially reduce the total test
time and simplify the test procedure by performing
steps (b) and (c) simultaneously by contacting the
10 sensing electrode with test solution to which has
been added the appropriate labelled secondary
receptors or labelled competing molecules for a
contact time of about 5-60 minutes. The
concentration of labelled secondary receptors or
15 labelled competing molecules added to the test
solution is typically 1-100 $\mu\text{g/ml}$ depending on their
type, specific features and required sensitivity of
the test.

To eliminate possible non-specific interactions
20 between the components of biological fluids under
test and the surface of the sensing electrode, and
also non-specific adsorption of labelled secondary
receptors or labelled competing molecules onto the
surface of the sensing electrode, which will distort
25 the results obtained, various blocking agents may be
added to the solution of labelled secondary receptors
or labelled competing molecules. Suitable blocking
agents include bovine serum albumin (0.5% - 5%),
human serum albumin (0.5 - 5wt.%), dilute normal
30 human or animal serum (5-10vol.%), gelatin (10-50
vol.%), etc. In so doing, interaction of the labelled
secondary receptors or labelled competing molecules
with the sensing electrode is accompanied by
simultaneous blocking of any free surface of the
35 sensing electrode.

In all of the detection methods of the invention use can be made of sensing electrodes containing immobilized/adsorbed adaptor molecules. In particular, the receptor molecules may be attached to the surface of the sensing electrode via biotin/avidin, biotin/streptavidin, protein A/antibody, protein G/antibody, FITC/anti-FITC or lectin/sugar binding interactions.

The use of 'universal' sensing electrodes containing adaptor molecules allows the detection methods to be performed in a 'one-pot' format. In this embodiment, the affinity reactions are performed in a homogeneous solution, providing maximum contact between the interacting molecules and ensuring maximum sensitivity and minimum duration of the test. In this case, the solution of receptors and the solution of labelled secondary receptors or labelled competing molecules are added simultaneously or sequentially to the test solution comprising the sample suspected of containing the analyte in a single reaction vessel. The concentrations of receptors and labelled secondary receptors or labelled competing molecules in the test solution are typically 0.1 - 100 $\mu\text{g/ml}$ and 1 - 100 $\mu\text{g/ml}$ respectively. The test solution is then incubated at 15-40°C for 5-60 minutes with or without continuous mixing to allow the binding reactions to take place. The sensing electrode containing the appropriate adaptor molecules is then brought into contact with the test solution, either by immersion into the vessel containing the test solution, or by placing a drop of test solution on the surface of the sensing electrode. The contact time between the sensing electrode and test solution is typically 3-30 minutes at 15-40°C. Measurement of the amount of analyte

- 26 -

bound on the sensing electrode is then performed using the "ion-step" procedure or by adding the appropriate enzyme substrate depending on whether the secondary receptors or competing molecules are
5 labelled with a charge or enzyme label.

Once all the affinity reaction steps are completed, an electrochemical measuring cell is assembled by bringing the sensing electrode and a reference electrode, connected by a measuring
10 instrument, into contact with an electrolyte solution (also referred to herein as a working solution) and the measuring device is used to record the sensing electrode potential relative to the reference electrode over a fixed time period. Commercially
15 available reference electrodes of suitable size, or electrodes purpose-designed for implementation of the declared invention, may be used as the reference. The measuring instrument is a standard potentiometric measuring instrument or potentiostat. PC-compatible
20 electronic measuring instruments purpose designed for implementation of the declared invention and controlled by custom software can also be used

For convenience the sensing electrode and reference electrode can be linked to the measuring
25 instrument by means of a special holder equipped with electrical contacts for connection of the sensing electrode and reference electrode and connected to the measuring instrument by a cable or other means. A holder integral with the measuring instrument could
30 also be used, making it possible to miniaturise the measuring system in terms of its overall dimensions.

Aqueous buffer solutions are used as the working solution : phosphate-saline, Tris-HCl, carbonate bicarbonate, acetate, borate, etc. The volume of
35 working solution in the electrochemical cell is

- 27 -

typically between 50 and 5000 μ l depending on the geometrical dimensions of the sensing electrode. The container for the buffer solution may be any suitably sized vessel in a material with minimal adsorption properties, e.g. the well of a standard microtiter plate. Another embodiment of the declared invention is a variant in which a low-volume ($< 1\text{cm}^3$) flow-through cell is used in conjunction with an integral holder for the sensing electrode and reference electrode, through which buffer solution can be pumped by means of a peristaltic pump or other means.

The potential of the sensing electrode relative to the reference electrode potential is recorded for a fixed time period using a chart recorder connected to a potentiometric measuring device or potentiostat, or by means of a special program where PC-compatible electronic instrumentation is used. In the latter case, the program measures the sensing electrode potential relative to the reference electrode potential at pre-determined time intervals (typically every 3-5 seconds for a total of 10-100 seconds) and displays the results in the form of points on the coordinates "sensing electrode signal - time".

Recording of sensing electrode potential relative to the reference electrode potential is carried out to determine the background potential value V_1 of the sensing electrode, and also to evaluate the background potential drift (γ) of the sensing electrode, which is calculated by linearisation of the curve "sensing electrode signal-time" obtained using the least squares method.

If the secondary receptors or competing molecules are conjugated with a charge label, the amount of analyte bound to the sensing electrode is

- 28 -

evaluated by changing the ionic strength of the electrolyte solution at constant pH, the so-called "ion-step" procedure.

5 In the ion-step procedure the ionic strength of the electrolyte solution may be modified (upwards or downwards) either by transferring the holder complete with sensing electrode and reference electrode from the initial working solution into a second working solution of the same composition but with a different ionic strength, or by adding a buffer solution of 10 different (higher or lower) ionic strength directly to the working solution in which the sensing electrode and reference electrode are immersed. If a flow through cell is used, the ionic strength of the electrolyte solution can be modified by expelling the 15 initial working solution from the cell using a buffer solution of different ionic strength.

Working solutions having different ionic strengths may be achieved by having different 20 concentrations of salts, e.g. KCl, Na₂SO₄, etc., the use of which is based on the fact that they dissociate completely when added to the solution and do not bias the pH of the solution. The concentration of salts in the working solution ranges from 0.01 to 25 0.1 M.

If the secondary receptors or competing molecules are conjugated with an enzyme it is not necessary to perform the "ion-step" procedure. Instead, the composition of the working solution is 30 modified by adding a suitable substrate for the enzyme. To this end, either the holder complete with sensing electrode and reference electrode can be transferred from the vessel containing the initial working solution to a vessel 35 containing working solution plus substrate, or the

- 29 -

substrate solution can be added directly to the original working solution in which the sensing electrode and reference electrode are immersed. If a flow-through cell is used, the composition of the working solution can be modified by expelling the initial working solution from the cell using a working solution containing substrate.

Substrates which may be used include ABTS ({2,2'-Azino-bis-[3-ethylbenzthiazoline-6-sulfonic acid]}), TMB (3, 3, 5, 5'-Tetraethylbenzidine), DAB (3, 3' Diaminobenzidine) (where the enzyme label is peroxidase), urea (where the enzyme label is urease), p-NPP (p-Nitrophenyl Phosphate), BCIP (5-bromo-4-chloro-3-indolylphosphate) (where the enzyme label is alkaline phosphatase).

The variation in sensing electrode potential relative to the reference electrode potential in response to a step change in ionic strength of the working solution or addition of an enzyme substrate is recorded for a fixed time period using a measuring instrument. Again, the recording is made either using a chart recorder connected to a potentiometric measuring device or potentiostat, or by means of a special program where PC-compatible electronic instrumentation is used. In the latter case, the program measures the sensing electrode potential relative to the reference electrode potential at pre-determined time intervals (typically every 3-5 seconds) and displays the results in the form of points on the coordinates "sensing electrode signal - time". Depending on the particular type of test, the time taken to record the variation in sensing electrode potential relative to reference electrode potential varies between 30 and 600 seconds.

In the case where the ionic strength of the

- 30 -

buffer solution is changed, the curve obtained for the variation in sensing electrode potential relative to the reference electrode potential usually takes the form of a parabola, and represents the response of the sensing electrode to the change in ionic strength of the buffer solution, which is modulated by the total charge (isoelectric point) of the electroconductive polymer film.

If the analysis is performed as a sandwich assay, the variation in total charge of the polymer film is directly proportional to the quantity of the analyte under test. However, if the analysis is performed as a competitive assay, the variation in total charge of the polymer film is generally inversely proportional to the quantity of analyte under test.

On completion of this stage in the procedure, the final value V_2 of sensing electrode potential relative to reference electrode potential is determined. The following quantitative characteristics of the change in sensing electrode potential relative to the reference electrode potential can then be calculated:

1. the area (integral) described by the curve obtained for the change in sensing electrode potential relative to reference electrode potential, S_2 :

$$S_2 = \int_{T_1}^{T_2} f_2(t) dt$$

where: $T_2 - T_1$ = total time period for recording of background potential drift or potential relative to the reference electrode; f_2 - curve of

- 31 -

"sensing electrode potential in millivolts
versus time"; t - current recording time;

and

5

2. difference in millivolts between the background
and final potential of the sensing electrode:

10

$$\delta = V_2 - V_1$$

15

Based on the quantitative characteristics of the
variation in sensing electrode potential in response
to a change in ionic strength or composition of the
working solution, a determination is made as to the
quantitative content of target analyte in the
test solution.

20

Using the values for γ , S_2 and/or δ obtained as
described above it is possible to re-calculate the
values to allow for the zero line drift γ , yielding
the values S_2^{γ} and/or δ^{γ} , on the basis of which a
determination is made of the quantity of target
analyte in test solution. The corrected values S_2^{γ}
and δ^{γ} may be compared with a calibration curve of
"analytical result versus amount of target analyte".
As would be readily apparent to persons skilled in
the art, data for construction of a calibration curve
can be obtained in a manner similar to the procedure
described above using a range of test solutions
containing known amounts of the target analyte.

30

In a still further aspect the invention provides
a method of electrochemical detection of an analyte
in a sample, which method comprises the steps of:

- (a) providing a sensing electrode comprising

- 32 -

an electrically conductive electrode coated with a layer of electroconductive polymer with avidin or streptavidin immobilized therein or adsorbed thereto, said avidin or streptavidin molecules being attached to receptor molecules capable of binding the analyte to be detected attached via a biotin/avidin or biotin/streptavidin binding interaction;

(b) contacting the sensing electrode with a test solution comprising the sample so that said desired analyte binds to said immobilized or adsorbed receptor molecules;

(c) monitoring the potential of the sensing electrode relative to a reference electrode when both are immersed in an electrolyte; and

(d) monitoring the potential difference of the sensing electrode relative to the reference electrode following a change in the ionic strength or composition of the electrolyte at constant pH.

This method of electrochemical detection is of use where the binding of the target analyte to the receptor causes a change in charge on the surface of the sensing electrode which is sufficiently large to be measurable without the need for a separate charge or enzyme label. In particular, this method is useful in the electrochemical detection of nucleic acids. Hybridisation of target nucleic acids to nucleic acid probes (e.g. oligonucleotides) attached to the surface of the sensing electrode is accompanied by a change in charge sufficient large to be detectable by the "ion-step" procedure. There is thus no need to use secondary receptors or competing molecules conjugated with charge label. Materials suspected of containing specific nucleic acids (e.g. biological fluids) may commonly be subjected to an amplification step (e.g. PCR) before being subjected

- 33 -

to the detection procedure. It is therefore within the scope of the invention to perform the electrochemical detection of specific nucleic acids on samples which have been subjected to an amplification procedure.

The present invention will be further understood with reference to the following non-limiting Examples together with the accompanying Figures in which the principal stages of its implementation are depicted.

Fig. 1A: schematically illustrates a sensing electrode consisting of a potentiometric electrode (1) coated with a layer of electroconductive polymer (2) with avidin or streptavidin molecules (3) immobilized in the polymer layer.

Fig. 1B: schematically illustrates a sensing electrode consisting of a potentiometric electrode (1) coated with a layer of electroconductive polymer (2) with avidin or streptavidin molecules (3) adsorbed onto the layer of polymer.

Fig. 2A: illustrates the process of rendering the sensing electrode specific to an analyte (in this case antigens, medium or high molecular weight substances) through a binding reaction between the avidin or streptavidin immobilized in the polymer layer and antibodies (4) conjugated with biotin (5).

Fig. 2B: illustrates the process of rendering the sensing electrode specific to the analyte under test (in this case antibodies) through a binding reaction between avidin or streptavidin immobilized in the polymer layer and antigen (6) conjugated with biotin

(5).

5 Fig. 2C: illustrates the process of rendering the sensing electrode specific to the analyte under test (in this case DNA molecules) through a binding reaction between avidin or streptavidin immobilized in the polymer layer and a DNA probe (7) conjugated with biotin (5).

10 Fig. 3A: shows the placement of the sensing electrode in contact with a test solution containing antigens (6) specific to biotinylated antibodies immobilized on the sensing electrode.

15 Fig. 3B: shows placement of the sensing electrode in contact with a test solution containing antibodies (4) specific to the biotinylated antigens immobilized on the sensing electrode.

20 Fig. 3C: shows placement of the sensing electrode in contact with a test solution containing DNA molecules (8) specific to the biotinylated DNA probes immobilized on the sensing electrode.

25 Fig. 4A: shows placement of the sensing electrode in contact with a solution of secondary receptors (9) conjugated with a charge label (10) and specific to the antigen under test (serological assay format, in which e.g. autoantibodies are determined by the use
30 of anti-isotype antibodies conjugated with a charge label).

35 Fig. 4B: shows placement of the sensing electrode in contact with a solution of secondary receptors (11) conjugated with a charge label (10) and specific to

- 35 -

the antibodies under test (sandwich assay format, in this case the secondary receptors are anti-isotype antibodies).

5 Fig. 5A: shows placement of the sensing electrode in contact with a solution of competing molecules (12) conjugated with a charge label (10) and specific to the biotinylated antibodies (competitive assay format).

10 Fig. 5B: shows placement of the sensing electrode in contact with a solution of competing molecules (13) conjugated with a charge label (10) and specific to the biotinylated antigens (competitive assay format).

15 Fig. 6A: shows placement of the sensing electrode in contact with a solution of secondary receptors (9) conjugated with an enzyme (14) and specific to the antigen under test (sandwich assay format).

20 Fig. 6B: shows placement of the sensing electrode in contact with a solution of secondary receptors (11) conjugated with an enzyme (14) and specific to the antibodies under test (serological assay format, in which e.g. autoantibodies are determined by the use of anti-isotype antibodies conjugated with an enzyme).

30 Fig. 7A: shows placement of the sensing electrode in contact with a solution of competing molecules (12) conjugated with an enzyme (14) and specific to the biotinylated antibodies (competitive assay format).

35 Fig. 7B: shows placement of the sensing electrode in contact with a solution of competing molecules (13)

- 36 -

conjugated with an enzyme (14) and specific to the biotinylated antigens (competitive assay format).

5 Fig. 8A: illustrates the steps of electrochemical analysis in a 'sequential' format with sequential placement of the sensing electrode in contact with a solution of biotinylated receptors [Fig. 8A1], with a test solution [Fig. 8A2], with a solution of labelled secondary receptors [Fig. 8A3], and subsequent
10 measurement of the sensing electrode potential relative to the potential of a reference electrode [Fig. 8A4].

15 Fig. 8B: illustrates the steps of electrochemical analysis in which the sensing electrode is first placed in contact with a solution of biotinylated receptors [Fig. 8B1], then the sensing electrode is placed in contact with a test solution to which a solution of labelled secondary receptors has been
20 added [Fig. 8B2], and the sensing electrode potential is then measured relative to the potential of a reference electrode [Fig. 8B3].

25 Fig. 8C: illustrates the steps of electrochemical analysis in a 'one-pot' format in which solutions of biotinylated receptors and labelled secondary receptors are added to a test solution [Fig. 8C1], then the sensing electrode is placed in contact with the test solution [Fig. 8C2], and the sensing
30 electrode potential is then measured relative to the potential of a reference electrode [Fig. 8C3].

35 Fig. 9: illustrates the typically shape of a curve of variation in sensing electrode potential for step-wise changes in the ionic strength or composition of

- 37 -

the working solution (on the coordinates "millivolts
-time") following incubation of the sensing electrode
with a test solution not containing any analyte
(curve 1), and following incubation of the sensing
5 electrode with a test solution containing analyte
specific to the biotinylated receptors (curve 2).

Fig. 10: shows a calibration curve of the difference
in millivolts between the background and final
10 potentials of the sensing electrode measured relative
to the reference electrode versus HBsAg concentration
in samples of blood serum.

Fig. 11: shows a curve of the difference in
15 millivolts between the background and final
potentials of the sensing electrode measured relative
to the reference electrode versus dilution of HBsAg-
positive blood serum.

20 The reagents, materials and equipment used in
the Examples were as follows:

Reagents and materials:

Pyrrole (> 98%) was purchased from Merck and before
25 use was purified twice by vacuum distillation, then
stored under N₂ in an opaque vessel at +4°C;

The following reagents were all purchased from Sigma
Chemical Co. (USA):

30 Potassium hydroxide (KOH), ACS reagent), sodium
hydroxide (NaOH, ACS reagent), sodium azide
(SigmaUltra), ceric sulphate (ACS reagent), potassium
chloride (SigmaUltra), sodium chloride (SigmaUltra),
Tris[hydroxymethyl]aminomethane (SigmaUltra), sodium
35 dodecylsulphate (SDS, >99%), sodium dextran sulphate

- 38 -

(mol.wt. ~8000), isopropyl alcohol (ACS reagent), acetone, hydrochloric acid (ACS reagent), chloric acid (ACS reagent), N,N-dimethyl formamide (ACS reagent), glycine buffer solution 0.2M), "Tris buffered saline tablets", "Phosphate buffered saline tablets", o-Phenylenediamine dihydrochloride tablets", bovine serum albumin (RIA grade, fraction V), frozen bovine serum, streptavidin (from *Streptomyces avidinii*), NHS-d-biotin, dimethyl sulfoxide (DMSO, ACS reagent), biotin-X-X-NHS, rabbit polyclonal antibodies to bovine albumin, conjugate of goat polyclonal antibodies to mouse IgG with urease, digoxin, mouse monoclonal anti-digoxin clone DI-22 biotin conjugate, peroxidase (100 units per mg solid), disposable dialysis bags (MWCO 1,000); Unless otherwise stated, phosphate buffered saline solution (PBS) was used throughout at pH 7.4.

Mouse monoclonal antibodies to Hepatitis B Surface Antigen (HBsAg) (5.7 mg/ml in phosphate buffered saline solution with 0.01% sodium azide), sheep polyclonal antibodies to mouse IgG (10.0 mg/ml in phosphate buffered saline solution with 0.01% sodium azide) and conjugate of mouse monoclonal antibodies to HBsAg with peroxidase (2.5 mg/ml in phosphate buffered saline solution with 0.01% sodium azide) were purchased from Sorbent-Service Ltd. (Russia);

Lyophilised insulin (bovine, ~20IU/mg) and mouse monoclonal antibodies to insulin (1.2 mg/ml in phosphate buffered saline solution), kindly contributed by members of the Cardiology Research Centre attached to the Russian Academy of Medical Sciences;

- 39 -

Preparation of lyophilised double-strand DNA-probe
(~1kb in length) biotinylated by nick-translation
[20], preparation of lyophilised double-strand DNA
complementary to biotinylated DNA-probe, preparation
5 of lyophilised double-strand DNA non-complementary to
biotinylated DNA-probe, preparation of lyophilised
DNA from salmon sperm and buffer solution for DNA
hybridisation, all kindly contributed by members of
the Scientific Research Institute of Biophysics
10 attached to the Ministry of Health.

Polybead® Sulphate Microspheres (2.5% Solids-Latex,
0.2 μm) were purchased from Polysciences Inc.;

15 Lavsan™ film (~500 μm thickness), purchased from
Vladimir Chemical Plant (Russia);

Chromium target dispersed in vacuum and photoresist
«FP-383», purchased from NIIPIK Institute (Russia);
20

Deionised water (reagent grade, resistance > 18 M Ω)
obtained using a Millipore Milli-RO/Milli-Q System;

Platinum wire, thickness ~ 0.5 mm;

25 Second British Working Standard for Hepatitis B
Surface Antigen (HBsAg concentration 0.50 iU/ml),
kindly contributed by the North London Blood
Transfusion Centre, UK;

30 Samples of HBsAg-positive human sera , kindly
contributed by the North London Blood Transfusion
Centre, UK.

- 40 -

Equipment:

UVN vacuum deposition unit (Russia);

«PNF-6Ts» photoresist application unit (Russia);

5

Self-produced photo-template (a photo-template which yields the electrode design shown in Figure 1, Figure 3 or Figure 4 of WO 96/02001 is suitable);

10 «STP-300» photo-exposure unit (Russia);

Self-made Soxhlet apparatus;

EU 18 dry heat cabinet (Jouan, France);

15

«PI-50.1» potentiostat-galvanostat with standard integrator and twin-coordinate recorder (Russia);

Two-channel recorder 2210 (LKB-Pribo, Sweden);

20

Checkmate pH meter with standard combination electrode (Mettler, Switzerland);

25 Self-produced Ag/AgCl semi-micro reference electrode, diameter ~ 2.5 mm and filled with saturated KCl solution;

Ag/AgCl reference electrode N° 476370 (Corning) ;

30 Purpose designed PC-compatible measuring instrument, including amplifier and analog-to-digital converter, controlled by custom software;

35 Purpose designed sensing electrode and reference electrode holder.

Example 1.

HBsAg determination: competitive assay; sample-diluted specimens; receptor-biotinylated monoclonal mouse anti-HBsAg; competing molecule-labelled sheep polyclonal anti-mouse IgG; charge label-latex.

1.1. Electrode substrates were prepared from 60 x 48mm Lavsan film, then washed in hot isopropanol and dried in isopropanol vapour. A 0.05 μ m layer of chromium was applied to the substrates by magnetron deposition. Photoresist was applied to the chromium layer by centrifugation and dried at +80°C for 20 minutes. The photoresist layer was exposed using ultraviolet light through a patterned phototemplate. The photoresist layer was developed in KOH solution, then dried at +100°C for 20 minutes. The chromium pattern was obtained by etching in ceric sulphate solution. The photoresist was removed using dimethylformamide, followed by rinsing and drying in isopropanol vapour. A 0.50 μ m layer of gold was applied to the chromium pattern by galvanic deposition from auric chloride solution, followed by rinsing and drying in isopropanol vapour.

1.2. The electrodes thus obtained were washed twice in 2-5% KOH solution for 30 minutes, then rinsed with deionised water and washed twice in acetone for 5 minutes, then air dried at room temperature for 20 minutes. The electrodes were then mounted in a fluoroplastic holder and placed in a Soxhlet vessel where they were washed in hot isopropyl alcohol for 0.5-2 hours. The holder complete with electrodes was then removed from the Soxhlet vessel and the electrodes were dried in isopropyl alcohol vapour. On completion of these procedures, the electrodes were

- 42 -

placed in a sealed glass vessel.

1.3. A storage solution for the sensing electrodes was made up by dissolving 8.0g of sodium chloride, 12.2g of Tris(hydroxymethyl)aminomethane, 0.2g of potassium chloride and 0.1g of sodium azide in 1 litre of deionised water.

1.4. Mouse monoclonal antibodies to HBsAg were biotinylated, as follows :

0.01M tris-saline buffered solution (pH 8.0) containing sodium azide was made by dissolving 20 tris buffered saline tablets and 0.15g of sodium azide in 1.50 litres of deionised water;

1.0mg NHS-d-biotin was dissolved in 1ml of DMSO;

176 μ l of the purchased mouse monoclonal antibodies to HBsAg (5.7mg/ml) were added to a microtube containing 824 μ l of 0.01M phosphate buffered saline solution;

50 μ l of NHS-d-biotin solution in DMSO were added to the solution obtained;

the microtube containing the mixture was placed in a thermomixer and held for 4 hours at a temperature of +22°C with continuous mixing;

the mixture was then dialysed at +4°C overnight against a 500-fold excess of 0.01M tris-saline buffered solution containing sodium azide;

the resultant solution of biotinylated

- 43 -

antibodies was divided into aliquots of small volume ($\sim 10\mu\text{l}$) and stored at $+4^{\circ}\text{C}$.

1.5. Sheep polyclonal antibodies to mouse IgG were
5 conjugated with latex microspheres, as follows :

10 a glycine buffered saline solution (pH 8.2) containing sodium azide was made up by adding 500ml of 0.2M glycine buffer solution to 500ml of deionised water, dissolving 8.5g of sodium chloride and 0.1g of sodium azide in the resultant mixture, and adjusting the pH to 8.2 with 0.1M NaOH solution;

15 $60\mu\text{l}$ of the purchased sheep polyclonal antibodies to mouse IgG (10mg/ml) were added to a microtube containing $940\mu\text{l}$ of glycine buffered saline solution (preferably the polyclonal antibodies are affinity purified before
20 labelling);

200 μl of a 2.5% suspension of Polybead[®] Sulphate Microspheres were added to the resultant solution;

25 the microtube containing the mixture was placed in a thermomixer and held for 30 minutes at a temperature of $37\pm 1^{\circ}\text{C}$ with continuous mixing;

30 the microtube containing the mixture was then cooled to room temperature and 0.01g of bovine serum albumin was added to it;

35 the resultant solution of labelled antibodies was divided into aliquots of small volume ($\sim 5\mu\text{l}$)

- 44 -

and stored at +4°C.

1.6. Prior to polymerisation, the monomer (e.g. pyrrole) is distilled in standard water cooled apparatus at atmospheric pressure at 135-140°C, and stored in a sealed opaque vessel under N₂ at -20°C to -5°C. The concentration of monomer in the electrochemical polymerisation solution is varied according to the type of test within the range 0.3 - 1.0 M.

In this example a solution was made up for electrochemical polymerisation of pyrrole as follows:

2.5ml of freshly-distilled pyrrole and 0.02g of SDS were dissolved in 20.0ml of deionised water; a phosphate-saline buffer tablet was dissolved in 200ml of deionised water and 4.0mg of streptavidin were dissolved in 2ml of the PBS; 1ml of streptavidin solution in PBS was added to the solution of pyrrole and SDS; the final solution was placed in an orbital mixer and mixed for 10 minutes.

1.7. The electrodeposition process is carried out in a triple-electrode electrochemical cell, including a working electrode, and reference electrode and an auxiliary (counter) electrode. The working electrode is a metal potentiometric electrode prepared as described above, the auxiliary electrode is a length of gold or platinum wire, and the reference is silver/silver chloride electrode.

Deposition is carried out using a potentiostat, applying a continuous voltage sweep on the working electrode. Depending on the desired thickness and properties of the polymer film, the lower potential sweep boundary, the upper potential sweep boundary, the voltage sweep rate and the number of sweep cycles are varied, typically from -500mV to +800mV, +1000mV to +2000mV (relative to the Ag/AgCl reference electrode), and 25 - 200 mV/sec. and 3-30 respectively.

In this example a polypyrrole film was formed by electrochemical deposition with binding of streptavidin on the electrode, as follows :

200 μ l of electrochemical polymerisation solution were placed in a well of a microtiter plate;

the electrode, platinum wire and semi-micro reference electrode, connected to the potentiostat, were immersed in the well;

a cyclical sweep of the electrode potential relative to the reference electrode was applied in the range +800 to +1800mV at a sweep rate of 150mV/sec.;

the process of formation of the polypyrrole film was monitored with reference to the volt-ampere curve using a twin-coordinate chart recorder connected to the corresponding outputs of the potentiostat, and with reference to the total quantity of electricity passing through the electrode using an integrator and chart recorder connected to the corresponding outputs of the

- 46 -

5 potentiostat. Throughout the deposition procedure checks are made to ensure that the quantity of electricity passing through the working electrode in the first and subsequent cycles does not differ by more than 15%;

10 on reaching the specified thickness of polypyrrole film (number of potential sweep cycles - 8; total quantity of electricity through the electrode - 750 mC), the process was stopped.

15 1.8. The sensing electrode coated in polypyrrole film with bound streptavidin was removed from the well, rinsed with deionised water followed by 0.01M phosphate-saline buffer solution (pH 7.4), and placed in a microtube with 300 μ l of storage solution, where it was stored at +4°C.

20 1.9. To obtain the required quantity of sensing electrodes steps 1.7-1.8 were repeated.

25 1.10. A series of 200 μ l samples of known HBsAg concentration were prepared in separate microtubes by diluting Second British Working Standard for Hepatitis B Surface Antigen in previously thawed bovine serum with a dilution factor of 2, 4, 8 and 10, adding 100, 150, 175 and 180 μ l of bovine serum to 100, 50, 25 and 20 μ l of Second British Working Standard for Hepatitis B Surface Antigen, 30 respectively. Pure bovine serum was used to provide a sample with zero HBsAg content.

35 1.11. 0.2ml of a suitably titered solution of the biotinylated mouse monoclonal antibodies to HBsAg was

- 47 -

added to 19.8ml of 0.01M phosphate buffered saline solution, thoroughly mixed in an orbital shaker, then dispensed into microtubes in aliquots of 200 μ l.

5 1.12. 0.1ml of a suitably titered solution of the labelled (latex conjugated) sheep polyclonal antibodies to mouse IgG was added to 19.9ml of 0.01M phosphate buffered saline solution, thoroughly mixed in an orbital mixer, then dispensed into microtubes
10 in aliquots of 200 μ l.

1.13. Working buffer solution N°1 was made up, as follows:

15 a phosphate-saline buffer tablet was dissolved in 200ml of deionised water;

2g of bovine serum albumin and 0.37g of KCl were dissolved in the solution obtained.

20 1.14. Working buffer solution N°2 was made up by dissolving a phosphate-saline buffer tablet in 200ml of deionised water.

25 1.15. The appropriate number of sensing electrodes coated in polypyrrole film with bound streptavidin were removed from the storage buffer solution and each placed in one of the microtubes containing the solution of biotinylated mouse
30 monoclonal antibodies to HBsAg (from step 1.11), and incubated for 10 minutes at room temperature.

1.16. On completion of 1.15, the sensing electrodes were removed from the microtubes
35 containing biotinylated antibodies solution and each

- 48 -

placed in one of the microtubes containing samples of known HBsAg concentration (from step 1.10); the microtubes with sensing electrodes were then placed in a thermomixer and held for 15 minutes at a temperature of $37\pm 1^{\circ}\text{C}$, mixing continuously.

1.17. On completion of 1.16, the sensing electrodes were removed from the microtubes containing the samples and placed in the microtubes containing latex conjugated sheep polyclonal antibodies to mouse IgG (from step 1.12), then placed in a rotary shaker and held for 5 minutes at room temperature, mixing continuously.

1.18. On completion of 1.17, the sensing electrodes were removed from the microtubes, rinsed for 3-5 seconds in 0.01M phosphate buffered saline solution, and each placed in a microtiter plate well filled with working buffer solution N°1.

1.19. The sensing electrode and reference electrode were connected to the electrical contacts of the holder connected to the PC-based measuring device, and the holder was positioned over the microtiter plate well filled with working buffer solution N°1 such that the sensing electrode and reference electrode were immersed in the solution.

1.20. The custom software was started and used to record the sensing electrode potential in millivolts relative to the reference electrode potential for a period of 30 seconds.

1.21. On completion of 1.20, the holder was positioned over a microtiter plate well filled with

working buffer solution N°2, in a manner similar to that described in 1.19.

5 1.22. The custom software was used to record the variation in millivolts of the sensing electrode potential relative to the reference electrode potential over a period of 100 seconds.

10 1.23. Using the custom software, the difference δ in millivolts between the background and final potential of the sensing electrode was calculated.

15 1.24. The operations described in 1.19 - 1.21 were repeated in sequence using the samples of known HBsAg concentration prepared during step 1.10.

20 1.25. Based on the results obtained during step 1.24, the custom software was used to plot the curve " δ against HBsAg concentration in the sample", (Fig. 10) and the lower threshold of absolute sensitivity of the sensing electrode system was determined from this curve.

25 Example 2.

HBsAg determination: competitive assay; sample-diluted specimens; receptor-biotinylated monoclonal mouse anti-HBsAg; competing molecule-labelled sheep polyclonal anti-mouse IgG; charge label-latex.

30

2.1. The procedures described in 1.1 - 1.5 were carried out.

35 2.2. A solution was made up for electrochemical polymerisation of pyrrole, as follows:

- 50 -

2.5ml of freshly-distilled pyrrole and 0.05g of SDS were dissolved in 20.0ml of deionised water;

2.3. A polypyrrole film was formed by electrochemical deposition, as follows :

200 μ l of electrochemical polymerisation solution were placed in a well of a microtiter plate;

the electrode, platinum wire and semi-micro reference electrode, connected to the potentiostat, were immersed in the well;

a cyclical sweep of the electrode potential relative to the reference electrode was applied in the range +800 to +2200mV at a sweep rate of 100mV/sec.;

the process of formation of the polypyrrole film was monitored with reference to the volt-ampere curve using an X-Y chart recorder connected to the corresponding outputs of the potentiostat, and with reference to the total quantity of electricity passing through the electrode using an integrator and chart recorder connected to the corresponding outputs of the potentiostat;

on reaching the specified thickness of polypyrrole film (number of potential sweep cycles - 6; total quantity of electricity through the electrode - 750 mC), the process was stopped.

2.4. The sensing electrode coated in polypyrrole film was removed from the well, rinsed with deionised

- 51 -

water followed by 0.01M phosphate-saline buffer solution (pH 7.4), and placed in a microtube with 300 μ l of storage solution, where it was stored at +4°C.

5

2.5. To obtain the required quantity of sensing electrodes, the procedures described in 2.1 - 2.4 were repeated.

10

2.6. A solution of streptavidin was made up by dissolving a phosphate-saline buffer tablet in 200ml of deionised water, and dissolving 1.0mg of streptavidin in the resultant solution.

15

2.7. Streptavidin was bound on the surface of the polypyrrole film covering the sensing electrode, as follows :

20

the streptavidin solution was dispensed into microtubes in 200 μ l aliquots;

25

the sensing electrodes coated with polypyrrole film were removed from the storage buffer solution, each placed in a microtube with streptavidin solution and incubated for 18 hours at +4°C;

30

the sensing electrodes were removed from the microtubes containing streptavidin solution, washed with a 0.01M phosphate buffered saline solution and each placed in storage buffer solution, then stored at +4°C.

35

2.8. A series of samples with known HBsAg concentration were prepared as described in 1.10.

- 52 -

2.9. 0.1ml of a suitably titered solution of the biotinylated mouse monoclonal antibodies to HBsAg was added to 19.9ml of 0.01M phosphate buffered saline solution, thoroughly mixed in a rotary shaker, then
5 dispensed into microtubes in aliquots of 200 μ l.

2.10. 0.1ml of a suitably titered solution of the labelled (latex conjugated) sheep polyclonal antibodies to mouse IgG was added to 19.9ml of 0.01M
10 phosphate buffered saline solution, thoroughly mixed in an orbital mixer, then dispensed into microtubes in aliquots of 200 μ l.

2.11. Working buffer solution N°1 was made up as
15 described in 1.13.

2.12. Working buffer solution N°2 was made up as described in 1.14.

2.13. The sensing electrodes coated in polypyrrole film with bound streptavidin were removed from the storage buffer solution and each placed in a microtube containing the solution of biotinylated mouse monoclonal antibodies to HBsAg (from step 2.9),
20 and incubated for 10 minutes at room temperature.
25

2.14. On completion of 2.13, the sensing electrodes were removed from the microtubes containing biotinylated antibodies solution and each
30 placed in one of the microtubes containing samples of known HBsAg concentration (from step 2.8); the microtubes with sensing electrodes were then placed in a thermomixer and held for 15 minutes at a temperature of 37 \pm 1°C, mixing continuously.
35

- 53 -

2.15. On completion of 2.14, the sensing electrodes were removed from the microtubes containing the samples and placed in the microtubes containing the solution of latex conjugated sheep polyclonal antibodies to mouse IgG (from step 2.10),
5 then placed in a rotary shaker and held for 5 minutes at room temperature, mixing continuously.

2.16. On completion of 2.15, the sensing electrodes were removed from the microtubes, rinsed
10 for 3-5 seconds in 0.01M phosphate buffered saline solution, and each placed in a microtiter plate well filled with working buffer solution N°1.

2.17. The sensing electrode and reference electrode were connected to the electrical contacts of the holder connected to the PC-based measuring instrument, and the holder was positioned over the microtiter plate well filled with working buffer
15 solution N°1 such that the sensing electrode and reference electrode were immersed in the solution.
20

2.18. The custom software was started and used to record the sensing electrode potential in millivolts
25 relative to the reference electrode potential for a period of 30 seconds.

2.19. On completion of 2.18, the holder was positioned over a microtiter plate well filled with working buffer solution N°2, in a manner similar to
30 that described in 2.17.

2.20. The custom software was used to record the variation in millivolts of the sensing electrode
35 potential relative to the reference electrode

- 54 -

potential over a period of 100 seconds.

2.21. Using the custom software, the difference
(δ) in millivolts between the background and final
5 potential of the sensing electrode was calculated.

2.22. The operations described in 2.17 - 2.20
were repeated in sequence using the samples of known
HBsAg concentration prepared at step 2.8.
10

2.23. Based on the results obtained at step 2.22,
the custom software was used to plot the calibration
curve " δ against HBsAg concentration in the sample".

2.24. A number of samples of HBsAg-positive blood
15 serum (containing an unknown concentration of HBsAg)
were each serially diluted in previously thawed
bovine serum to prepare a series of samples with
dilution factors of 10, 100, 1000, 5000 and 10 000. A
20 200 μ l aliquot of each dilution was placed in a
separate microtube.

2.25. The procedure described in steps 2.13-2.21
was used to determine the concentration of HBsAg in
25 each of the dilutions and these results, together
with the calibration curve obtained in step 2.23 were
used to calculate the concentration of HBsAg in the
original (undiluted) samples of blood serum (Fig.
11).
30

Example 3.

Anti-albumin antibody determination: competitive
assay; sample-rabbit polyclonal antibodies against
35 albumin; receptor-biotinylated bovine serum albumin;

- 55 -

competing molecule-labelled rabbit polyclonal antibodies to albumin; charge label-latex.

5 3.1. The procedures described in 1.1 - 1.3 were carried out.

10 3.2. Bovine serum albumin (BSA) was biotinylated as described in 1.4. The resultant solution of biotinylated BSA was divided into aliquots of small volume ($\sim 10\mu\text{l}$) and stored at $+4^\circ\text{C}$.

15 3.3. Rabbit polyclonal antibodies to bovine albumin were conjugated with latex microspheres following the procedure described in 1.5. The resultant solution of labelled antibodies was divided into aliquots of small volume ($\sim 5\mu\text{l}$) and stored at $+4^\circ\text{C}$.

20 3.4. A solution was made up for electrochemical polymerisation of pyrrole, as described in 2.2.

3.5. A polypyrrole film was formed by electrochemical deposition, as described in 2.3.

25 3.6. The sensing electrode coated in polypyrrole film was removed from the well, rinsed with deionised water followed by 0.01M phosphate-saline buffer solution (pH 7.4), and placed in a microtube with $300\mu\text{l}$ of storage solution, where it was stored at $+4^\circ\text{C}$.

30 3.7. To obtain the required quantity of sensing electrodes, the procedures described in 3.1 - 3.6 were repeated.

35 3.8. A solution of streptavidin was made up as

- 56 -

described in 2.6.

3.9. Streptavidin was bound on the surface of the polypyrrole film covering the sensing electrode, as
5 described in 2.7.

3.10. A series of samples with known concentration of unlabelled rabbit polyclonal antibodies to bovine albumin were prepared, as
10 follows:

the purchased sample of rabbit polyclonal antibodies to bovine albumin was dialysed at +4°C overnight against a 500-fold excess of 0.01M
15 phosphate buffered saline solution;

the resultant solution of rabbit polyclonal antibodies to bovine albumin in 0.01M phosphate buffered saline solution was serially diluted
20 with 0.01M phosphate buffered saline solution at dilution factors of 10, 20, 50, 100, 1000 and 5000;

200µl aliquots of each of the diluted samples
25 were placed in separate microtubes.

3.11. 0.8ml of a suitably diluted solution of biotinylated BSA was added to 19.2ml of 0.01M phosphate buffered saline solution, thoroughly mixed
30 in a rotary shaker, then dispensed into microtubes in aliquots of 200µl.

3.12. 0.1ml of a suitably titered solution of labelled (latex conjugated, as described above)
35 rabbit polyclonal antibodies to bovine albumin was

- 57 -

added to 19.9ml of 0.01M phosphate buffered saline solution, thoroughly mixed in an orbital mixer, then dispensed into microtubes in aliquots of 200 μ l.

5 3.13. Working buffer solution N°1 was made up, as follows:

a phosphate-saline buffer tablet was dissolved in 200ml of deionised water;

10

0.37g of KCl were dissolved in the solution obtained.

15 3.14. Working buffer solution N°2 was made up as described in 1.14.

20 3.15. The sensing electrodes coated in polypyrrole film with bound streptavidin were removed from the storage buffer solution and each placed in one of the microtubes containing 200 μ l of biotinylated BSA solution (from step 3.11), and incubated for 25 minutes at room temperature.

25 3.16. On completion of 3.15, the sensing electrodes were removed from the microtubes containing biotinylated BSA solution and each placed in one of the microtubes containing samples with known concentration of unlabelled rabbit polyclonal antibodies to bovine albumin (from step 3.10); the
30 microtubes with sensing electrodes were then placed in a thermomixer and held for 25 minutes at a temperature of 37 \pm 1°C, mixing continuously.

35 3.17. On completion of 3.16, the sensing electrodes were removed from the microtubes

- 58 -

containing the samples and transferred to microtubes containing the solution of latex conjugated rabbit polyclonal antibodies to bovine albumin (from step 3.12), then placed in a rotary shaker and held for 10 minutes at room temperature, mixing continuously.

3.18. On completion of 3.17, the sensing electrodes were removed from the microtubes, rinsed for 3-5 seconds in 0.01M phosphate buffered saline solution, and each placed in a microtiter plate well filled with working buffer solution N°1.

3.19. The sensing electrode and reference electrode were connected to the electrical contacts of the holder connected to the PC-based measuring instrument, and the holder was positioned over the microtiter plate well filled with working buffer solution N°1 such that the sensing electrode and reference electrode were immersed in the solution.

3.20. The custom software was started and used to record the sensing electrode potential in millivolts relative to the reference electrode potential over a period of 100 seconds.

3.21. On completion of 3.20, the holder was positioned over a microtiter plate well filled with working buffer solution N°2, in a manner similar to that described in 3.19.

3.22. The custom software was used to record the variation in millivolts of the sensing electrode potential relative to the reference electrode potential over a period of 200 seconds.

- 59 -

3.23. Using the custom software, the area (integral) S_2 described by the curve of sensing electrode potential variation versus reference electrode potential was calculated.

5

3.24. The operations described in 3.19 - 3.23 were repeated in sequence using the samples with known concentration of unlabelled rabbit polyclonal antibodies to bovine albumin prepared at step 3.10.

10

3.25. Based on the results obtained at step 3.24, the custom software was used to plot the calibration curve " S_2 against concentration of unlabelled rabbit polyclonal antibodies to bovine albumin in the sample".

15

Example 4.

HBsAg determination; sandwich assay; sample-sample with known HBsAg concentration; receptor-biotinylated mouse monoclonal antibodies to HBsAg; labelled mouse monoclonal antibodies to HBsAg; label-peroxidase.

20

4.1. The procedures described in 1.1 - 1.4 were carried out.

25

4.2. A solution was made up for electrochemical polymerisation of pyrrole, as described in 2.2.

30

4.3. A polypyrrole film was formed by electrochemical deposition, as described in 2.3.

4.4. The sensing electrode coated in polypyrrole film was removed from the well, rinsed with deionised water followed by 0.01M phosphate-saline buffer

35

- 60 -

solution (pH 7.4), and placed in a microtube with 300 μ l of storage solution, where it was stored at +4°C.

5 4.5. To obtain the required quantity of sensing electrodes, the procedures described in 4.1-4.4 were repeated.

10 4.6. A solution of streptavidin was made up as described in 2.6.

15 4.7. Streptavidin was bound on the surface of the polypyrrole film covering the sensing electrode, as described in 2.7.

15 4.8. A series of samples with known HBsAg concentration were prepared, as described in 1.10.

20 4.9. 0.2ml of a suitably titrated solution of the biotinylated mouse monoclonal antibodies to HBsAg was added to 19.8ml of 0.01M phosphate buffered saline solution, thoroughly mixed in a rotary shaker, then dispensed into microtubes in aliquots of 200 μ l.

25 4.10. 5ml of previously thawed bovine serum were added to 15ml of 0.01M phosphate buffered saline solution, and 0.4ml of a suitably titrated solution of purchased peroxidase conjugated mouse monoclonal antibodies to HBsAg was added to 19.6ml of the
30 resultant solution, which was then thoroughly mixed in a rotary shaker and dispensed into microtubes in aliquots of 200 μ l.

35 4.11. Working buffer solution N°1 was made up by dissolving a phosphate-saline buffer tablet in 200ml

- 61 -

of deionised water.

4.12. Working buffer solution N°2 was made up, as follows:

5

an o-Phenylenediamine dihydrochloride tablet and a urea hydrogen peroxide/buffer tablet were dissolved in 20ml of deionised water;

10

0.1ml of the solution obtained was added to 19.9ml of 0.01M phosphate buffered saline solution, thoroughly mixed in a rotary shaker, then placed in an opaque glass vessel and stored at +4°C until the start of the test.

15

4.13. The sensing electrodes coated in polypyrrole film with bound streptavidin were removed from the storage buffer solution and each placed in a microtube containing 200 μ l of the solution of biotinylated mouse monoclonal antibodies to HBsAg (from step 4.9) and incubated for 5 minutes at room temperature.

25

4.14. On completion of 4.13, the sensing electrodes were removed from the microtubes containing biotinylated antibodies solution and placed in microtubes containing samples with known HBsAg concentration (from step 4.8); the microtubes with sensing electrodes were then placed in a thermomixer and held for 10 minutes at a temperature of 37 \pm 1°C, mixing continuously.

30

4.15. On completion of 4.14, the sensing electrodes were removed from the microtubes containing the samples and placed in microtubes

35

- 62 -

containing the solution of peroxidase-conjugated mouse monoclonal antibodies to HBsAg (from step 4.10), then placed in a rotary shaker and held for 5 minutes at room temperature, mixing continuously.

5

4.16. On completion of 4.15, the sensing electrodes were removed from the microtubes, rinsed for 3-5 seconds in 0.01M phosphate buffered saline solution, and each placed in a microtiter plate well filled with working buffer solution N°1.

10

4.17. The sensing electrode and reference electrode were connected to the electrical contacts of the holder connected to the PC-based measuring instrument, and the holder was positioned over the microtiter plate well filled with working buffer solution N°1 such that the sensing electrode and reference electrode were immersed in the solution.

15

4.18. The custom software was started and used to record the sensing electrode potential in millivolts relative to the reference electrode potential over a period of 50 seconds.

20

4.19. On completion of 4.18, the holder was positioned over a microtiter plate well filled with working buffer solution N°2, in a manner similar to that described in 4.17.

25

4.20. The custom software was used to record the variation in millivolts of the sensing electrode potential relative to the reference electrode potential over a period of 100 seconds.

30

4.21. Using the custom software, the difference

35

- 63 -

(δ) in millivolts between the background and final potential of the sensing electrode was calculated.

4.22. The operations described in 4.17 - 4.21
5 were repeated in sequence using the samples of known HBsAg concentration prepared at step 4.8.

4.23. Based on the results obtained at step 4.22,
the custom software was used to plot the calibration
10 curve " δ against HBsAg concentration in the sample".

4.24. A series of diluted blood serum samples
were prepared as described in 2.24.

15 4.25. The procedure described in steps 4.13 -
4.21 was used to determine the concentration of HBsAg
in each of the diluted samples prepared in 4.24 and
these results, together with the calibration curve
obtained in step 4.23 were used to calculate the
20 concentration of HBsAg in the original (undiluted)
samples of blood serum.

Example 5.

25 HBsAg determination; sandwich assay; sample-sample
with known HBsAg concentration; receptor-biotinylated
mouse monoclonal antibodies to HBsAg; labelled mouse
monoclonal antibodies to HBsAg; label-peroxidase;
"sequential assay".

30

5.1. The procedures described in 1.1 - 1.4 were
carried out.

5.2. A solution was made up for electrochemical
35 polymerisation of pyrrole, as described in 2.2.

- 64 -

5.3. A polypyrrole film was formed by electrochemical deposition, as described in 2.3.

5.4. The sensing electrode coated in polypyrrole film
5 was removed from the well, rinsed with deionised water followed by 0.01M phosphate-saline buffer solution (pH 7.4), and placed in a microtube with 300 μ l of storage solution, where it was stored at +4°C.

10

5.5. To obtain the required quantity of sensing electrodes, the procedures described in 5.1- 5.4 were repeated.

15 5.6. A solution of streptavidin was made up as described in 2.6.

5.7. Streptavidin was bound on the surface of the polypyrrole film covering the sensing electrode, as
20 described in 2.7.

5.8. A series of samples with known HBsAg concentration were prepared, as described in 1.10.

25 5.9. 0.5ml of a solution of biotinylated mouse monoclonal antibodies to HBsAg was added to 19.5ml of 0.01M phosphate buffered saline solution, thoroughly mixed in a rotary shaker, then dispensed into microtubes in aliquots of 200 μ l.

30

5.10. 1.7ml of a solution of peroxidase-labelled mouse monoclonal antibodies to HBsAg was added to 18.3ml of 0.01M phosphate buffered saline solution, thoroughly mixed in an orbital mixer and dispensed
35 into microtubes in aliquots of 200 μ l.

- 65 -

5.11. Working buffer solution N°1 was made up as described in 4.11.

5.12. Working buffer solution N°2 was made up as
5 described in 4.12.

5.13. The sensing electrodes coated in polypyrrole film with bound streptavidin were removed from the storage buffer solution and each placed in a
10 microtube containing the solution of biotinylated mouse monoclonal antibodies to HBsAg (from step 5.9), and incubated for 5 minutes at room temperature.

5.14. Simultaneously with step 5.13, 10 μ l of a
15 suitably titered solution of the purchased peroxidase-labelled mouse monoclonal antibodies to HBsAg were added to each sample with known HBsAg concentration (from step 5.8), having first removed 10 μ l from the sample; the microtubes and samples were
20 then placed in a thermomixer at 37 \pm 1°C for 5-10 minutes.

5.15. On completion of 5.13 - 5.14, the sensing electrodes were removed from the microtubes
25 containing the solution of biotinylated antibodies and placed in the microtubes containing samples with known HBsAg concentration (from step 5.14) then held in the thermomixer for 15 minutes at 37 \pm 1°C, mixing continuously.

30 5.16. On completion of 5.15, the sensing electrodes were removed from the microtubes, rinsed for 3-5 seconds in 0.01M phosphate buffered saline solution, and each placed in a microtiter plate well
35 filled with working buffer solution N°1.

- 66 -

5.17. The sensing electrode and reference electrode were connected to the electrical contacts of the holder connected to the PC-based measuring instrument, and the holder was positioned over the microtiter plate well filled with working buffer solution N°1 such that the sensing electrode and reference electrode were immersed in the solution.

5.18. The custom software was started and used to record the sensing electrode potential in millivolts relative to the reference electrode potential over a period of 50 seconds.

5.19. On completion of 5.18, the holder was positioned over a microtiter plate well filled with working buffer solution N°2, in a manner similar to that described in 5.17.

5.20. The custom software was used to record the variation in millivolts of the sensing electrode potential relative to the reference electrode potential over a period of 200 seconds.

5.21. Using the custom software, the area (integral) S_2 described by the curve of sensing electrode potential variation versus reference electrode potential was calculated.

5.22. The operations described in 5.17 - 5.21 were repeated in sequence using the samples with known HBsAg concentration prepared at step 5.8.

5.23. Based on the results obtained at step 5.22, the custom software was used to plot the calibration curve " S_2 against HBsAg concentration in the sample".

- 67 -

5.24. A series of diluted blood serum samples were prepared as described in 2.24.

5.25. The procedure described in steps 5.13 -
5 5.21 was used to determine the concentration of HBsAg
in each of the diluted samples prepared in 5.24 and
these results, together with the calibration curve
obtained in step 5.23, were used to calculate the
concentration of HBsAg in the original (undiluted)
10 samples of blood serum.

Example 6.

HBsAg determination; sandwich assay; sample-sample
15 with known HBsAg concentration; receptor-biotinylated
mouse monoclonal antibodies to HBsAg; labelled mouse
monoclonal antibodies to HBsAg; label-peroxidase;
"one-pot assay".

20 6.1 The procedures described in 1.1 - 1.4 were
carried out.

6.2. A solution was made up for electrochemical
polymerisation of pyrrole, as described in 2.2.

25 6.3. A polypyrrole film was formed by electrochemical
deposition, as described in 2.3.

6.4. The sensing electrode coated in polypyrrole film
30 was removed from the well, rinsed with deionised
water followed by 0.01M phosphate-saline buffer
solution (pH 7.4), and placed in a microtube with
300 μ l of storage solution, where it was stored at
+4°C.

35

- 68 -

6.5. To obtain the required quantity of sensing electrodes, the procedures described in 6.1 - 6.4 were repeated.

5 6.6. A solution of streptavidin was made up as described in 2.6.

10 6.7. Streptavidin was bound on the surface of the polypyrrole film covering the sensing electrode, as described in 2.7.

6.8. A series of samples with known HBsAg concentration were prepared, as described in 1.10.

15 6.9. 2.5ml of a suitably titrated solution of the biotinylated mouse monoclonal antibodies to HBsAg was added to 17.5ml of 0.01M phosphate buffered saline solution, thoroughly mixed in a rotary shaker, then dispensed into microtubes in aliquots of 200 μ l.

20 6.10. 1.7ml of a suitably titrated solution of the purchased peroxidase-labelled mouse monoclonal antibodies to HBsAg was added to 18.3ml of 0.01M phosphate buffered saline solution, thoroughly mixed in a rotary shaker and dispensed into microtubes in aliquots of 200 μ l.

25 6.11. Working buffer solution N°1 was made up as described in 4.11.

30 6.12. Working buffer solution N°2 was made up as described in 4.12.

35 6.13. 10 μ l of a solution of biotinylated mouse monoclonal antibodies to HBsAg (from step 6.9) and

- 69 -

10 μ l of peroxidase-labelled mouse monoclonal
antibodies to HBsAg (from step 6.10) were added to
each sample of known HBsAg concentration, having
first removed 20 μ l from the sample; the microtubes
5 and samples were then placed in a thermomixer, where
they were incubated for 10 minutes at $37 \pm 1^\circ\text{C}$, mixing
continuously.

6.14. On completion of 6.13, the sensing
10 electrodes coated in polypyrrole film with bound
streptavidin were removed from the storage buffer
solution, each placed in the microtubes containing
samples with known HBsAg concentration (from step
6.13), then held in the thermomixer for 5 minutes at
15 a temperature of $37 \pm 1^\circ\text{C}$, mixing continuously.

6.15. On completion of 6.14, the sensing
electrodes were removed from the microtubes, rinsed
for 3-5 seconds in 0.01M phosphate buffered saline
20 solution, and each placed in a microtiter plate well
filled with working buffer solution N°1.

6.16. The sensing electrode and reference
electrode were connected to the electrical contacts
25 of the holder connected to the PC-based measuring
instrument, and the holder was positioned over the
microtiter plate well filled with working buffer
solution N°1 such that the sensing electrode and
reference electrode were immersed in the solution.

30
6.17. The custom software was started and used to
record the sensing electrode potential in millivolts
relative to the reference electrode potential over a
period of 100 seconds.

35

- 70 -

6.18. On completion of 6.17, the holder was positioned over a microtiter plate well filled with working buffer solution N°2, in a manner similar to that described in 6.16.

5

6.19. The custom software was used to record the variation in millivolts of the sensing electrode potential relative to the reference electrode potential over a period of 200 seconds.

10

6.20. Using the custom software, the area (integral) S_2 described by the curve of sensing electrode potential variation versus reference electrode potential was calculated.

15

6.21. The operations described in 6.16 - 6.20 were repeated in sequence using the samples with known HBsAg concentration prepared at step 6.8.

20

6.22. Based on the results obtained at step 6.21, the custom software was used to plot the calibration curve " S_2 - HBsAg concentration in the sample".

25

6.23. A series of diluted blood serum samples were prepared as described in 2.24.

30

6.24. The procedure described in steps 6.13 - 6.21 was used to determine the concentration of HBsAg in each of the diluted samples prepared in 6.23 and these results, together with the calibration curve obtained in step 6.22, were used to calculate the concentration of HBsAg in the original (undiluted) samples of blood serum.

35

- 71 -

Example 7.

Insulin determination; competitive assay; sample-
samples with known insulin conc; receptor-
biotinylated mouse monoclonal antibodies to insulin;
5 competing molecule-labelled polyclonal goat anti-
mouse IgG antibodies; label-urease

7.1. The procedures described in 1.1 - 1.3 were
carried out.

10

7.2. Biotinylation of mouse monoclonal antibodies to
insulin was carried out as described in 1.4. The
resultant solution of biotinylated mouse monoclonal
antibodies to insulin was divided into aliquots of
15 small volume ($\sim 10\mu\text{l}$) and stored at $+4^\circ\text{C}$.

7.3. A solution was made up for electrochemical
polymerisation of pyrrole, as described in 2.2.

20 7.4. A polypyrrole film was formed by electrochemical
deposition, as described in 2.3.

7.5. The sensing electrode coated in polypyrrole film
was removed from the well, rinsed with deionised
25 water followed by 0.01M phosphate-saline buffer
solution (pH 7.4), and placed in a microtube with
300 μl of storage solution, where it was stored at
 $+4^\circ\text{C}$.

30 7.6. To obtain the required quantity of sensing
electrodes, the procedures described in 7.4-7.5 were
repeated.

7.7. A solution of streptavidin was made up as
35 described in 2.6.

- 72 -

7.8. Streptavidin was bound on the surface of the polypyrrole film covering the sensing electrode, as described in 2.7.

- 5 7.9. A series of samples with known insulin concentration were prepared, as follows:

10 1.12g of potassium chloride and 1.0g of bovine serum albumin were dissolved in 100ml of deionised water;

 100 μ g of lyophilised insulin were dissolved in 200 μ l of the solution obtained;

15 the insulin solution obtained was sequentially diluted with deionised water with potassium chloride and bovine serum albumin at dilution factors of 10, 20, 50, 100, 1000, 5000 and 10,000 times;

20 200 μ l aliquots of each of the diluted samples were placed in separate microtubes.

25 7.10. 0.8ml of a suitably titered solution of the biotinylated mouse monoclonal antibodies to insulin were added to 19.2ml of 0.01M phosphate buffered saline solution, thoroughly mixed in a rotary shaker, then aliquotted into microtubes in quantities of 200 μ l.

30 7.11. 0.02 ml of purchased urease conjugated goat polyclonal antibodies to mouse IgG was added to 19.98ml of 0.01M phosphate buffered saline solution, thoroughly mixed in a rotary shaker and aliquotted
35 into microtubes in quantities of 200 μ l.

- 73 -

7.12. Working buffer solution N°1 was made up by dissolving 2.24g of potassium chloride in 200ml of deionised water.

5 7.13. Working buffer solution N°2 was made up by dissolving 0.012g of urea in 20ml of working buffer solution N°1.

10 7.14. The sensing electrodes coated in polypyrrole film with bound streptavidin were removed from the storage solution, each placed in a microtube with the solution of biotinylated mouse monoclonal antibodies to insulin (from step 7.10), and incubated for 10 minutes.

15 7.15. On completion of 7.14, the sensing electrodes were removed from the microtubes with the solution of biotinylated antibodies and placed in microtubes containing samples of known insulin
20 concentration (from step 7.9), then placed in a thermomixer and held for 15 minutes at a temperature of $37\pm 1^{\circ}\text{C}$, mixing continuously.

25 7.16. On completion of 7.15, the sensing electrodes were removed from the microtubes containing the samples and placed in microtubes containing the solution of urease conjugated goat polyclonal antibodies to mouse IgG (from step 7.11), then placed in a rotary shaker and held for 10
30 minutes at room temperature, mixing continuously.

35 7.17. On completion of 7.16, the sensing electrodes were removed from the microtubes, rinsed for 3-5 seconds in deionised water with potassium chloride and bovine serum albumin, and each placed in

microtiter plate well filled with working buffer N°1.

5 7.18. The sensing electrode and reference electrode were connected to the electrical contacts of the holder connected to the PC-based measuring device, and the holder was positioned over the microtiter plate well filled with working buffer solution N°1 such that the sensing electrode and reference electrode were immersed in the solution.

10 7.19. The custom software was started and used to record the sensing electrode potential in millivolts relative to the reference electrode potential over a period of 200 seconds.

15 7.20. On completion of 7.19, the holder was positioned over a microtiter plate well filled with working buffer solution N°2, in a manner similar to that described in 7.18.

20 7.21. The custom software was used to record the variation in millivolts of the sensing electrode potential relative to the reference electrode potential over a period of 400 seconds.

25 7.22. Using the custom software, the area (integral) S_2 described by the curve of sensing electrode potential variation versus reference electrode potential was calculated.

30 7.23. The operations described in 7.18 - 7.22 were repeated in sequence using the samples with known insulin concentration prepared at step 7.9.

35 7.24. Based on the results obtained at step 7.23,

the custom software was used to plot the calibration curve "S₂ against insulin concentration in the sample".

5

Example 8.

Nucleic acid hybridisation.

8.1. The procedures described in 1.1 - 1.3 were
10 carried out.

8.2. A solution was made up for electrochemical polymerisation of pyrrole, as described in 2.2.

15 8.3 A polypyrrole film was formed by electrochemical deposition, as described in 2.3.

8.4. The sensing electrode coated in polypyrrole film was removed from the well, rinsed with deionised
20 water followed by 0.01 M phosphate saline buffer solution (pH 7.4), and placed in a microtube with 300µl of storage solution, where it was stored at +4°C.

25 8.5. To obtain the required quantity of sensing electrodes, the procedures described in 8.3 - 8.4 were repeated.

8.6. A solution of streptavidin was made up by
30 dissolving a phosphate buffered saline tablet in 200ml of deionised water and dissolving 5.0mg of streptavidin in the solution obtained.

35 8.7. Streptavidin was bound on the surface of the polypyrrole film covering the sensing electrode, as

- 76 -

follows:

the streptavidin solution was dispensed into
microtubes in aliquots of 300 μ l;

5

the sensing electrodes coated with polypyrrole
film were removed from the storage solution,
each placed in a microtube containing
streptavidin solution and incubated for 24 hours
at +4°C;

10

the sensing electrodes were removed from the
microtubes containing streptavidin solution,
rinsed with 0.01M phosphate buffered saline
solution and twice with deionised water
containing 0.01% sodium azide and 0.15M
potassium chloride: each sensing electrode was
then placed in storage solution and stored at
+4°C.

15

20

8.8 A solution of biotinylated single-strand DNA
probe was prepared, as follows:

1mg of lyophilised preparation of biotinylated
double strand DNA probe (~1kb in length) was
dissolved in 1ml of deionised water, and the
solution obtained was placed in a microtube.

25

the microtube containing the DNA probe solution
was placed in a water bath where it was
incubated for 5-8 minutes at +100°C;

30

the microtube containing the DNA probe was
transferred to a vessel containing ice, where it
was rapidly cooled to 0°C;

35

- 77 -

the microtube containing the DNA probe was then transferred to a freezer where it was stored frozen at -20°C .

- 5 8.9. A solution of single-strand DNA complementary to biotinylated DNA-probe was prepared, as follows:

10 10mg of lyophilised preparation of double-strand DNA complementary to biotinylated DNA-probe was dissolved in 1ml of deionised water, and the solution obtained was placed in a microtube;

15 the microtube containing the DNA solution was placed in a water bath, where it was incubated for 5-8 minutes at $+100^{\circ}\text{C}$;

20 the microtube containing the DNA solution was transferred to a vessel containing ice, where it was rapidly cooled to 0°C ;

25 the microtube containing the DNA solution was then transferred to a freezer where it was stored frozen at -20°C .

- 25 8.10. A solution of single-strand DNA non-complementary to biotinylated DNA probe was prepared as described in 8.9.

- 30 8.11 Working buffer solution N°1 was made up as follows:

a phosphate buffered saline tablet was dissolved in 200ml of deionised water;

35 2g of bovine serum albumin, 0.37g of potassium

- 78 -

chloride and 0.12g of sodium citrate were dissolved in the solution obtained.

8.12. Working buffer solution N°2 was made up as follows:

a phosphate buffered saline tablet was dissolved in 200ml of deionised water;

2g of bovine serum albumin and 1g of sodium dextran sulphate were dissolved in the solution obtained.

8.13. The sensing electrodes coated in polypyrrole film with bound streptavidin were removed from the deionised water containing 0.01% sodium azide and 0.15M potassium chloride, and 20 μ l of single-strand DNA probe solution previously thawed and warmed to room temperature was applied to working the surface of each sensing electrode.

8.14. On completion of 8.13, the sensing electrodes were placed in a humidity chamber where they were incubated for 60 minutes at +44°C.

8.15. On completion of 8.14, the sensing electrodes were removed from the humidity chamber and each placed in a microtube containing 200 μ l of initial buffer solution for DNA hybridisation, where they were held for a short period of time at +4°C. (The DNA hybridisation buffer may be any standard hybridisation buffer known in the art, see Sambrook, J., Fritsch, E. F. and Maniatis, T. (1989) *Molecular Cloning: A Laboratory Manual*, 2nd Edition, Cold Spring Harbor Laboratory Press, Cold Spring Harbor,

- 79 -

NY, USA)

8.16. Samples containing single-strand DNA
complementary to biotinylated DNA probe were
5 prepared, as follows:

10mg of a preparation of lyophilised DNA from
salmon sperm was dissolved in 10ml of initial
buffer solution for DNA hybridisation.

10

10µl of the solution of single-strand DNA
complementary to biotinylated DNA-probe
previously thawed and warmed to room temperature
were added to 0.99ml of the solution obtained:

15

the resulting solution was thoroughly mixed in a
rotary shaker and dispensed into microtubes
aliquots of 200µl.

20

8.17. Samples containing single-strand DNA non-
complementary to biotinylated DNA probe were
prepared, as follows:

25

10mg of a preparation of lyophilised DNA from
salmon sperm was dissolved in 10ml of initial
buffer solution for DNA hybridisation;

30

100µl of the solution of single-strand DNA non-
complementary to biotinylated DNA probe
previously thawed and warmed to room temperature
were added to 0.9ml of the solution obtained;

35

the resulting solution was thoroughly mixed in a
rotary shaker and dispensed into microtubes in

- 80 -

aliquots of 200 μ l.

8.18. Half of the sensing electrodes with immobilised biotinylated single-strand DNA-probe were removed from the microtubes containing initial buffer solution for DNA hybridisation and placed in the microtubes with samples containing DNA complementary to biotinylated DNA-probe; the microtubes containing the sensing electrodes were then placed in a thermomixer and held for 120 minutes at +42°C mixing continuously.

8.19. On completion of 8.18, the sensing electrodes were removed from the microtubes, rinsed for 3-5 seconds in working buffer solution N°1 and each placed in the well of a microtiter plate filled with working buffer solution N°1.

8.20. The sensing electrode and reference electrode were connected to the electrical contacts of the holder connected to the PC-based measuring device, and the holder was positioned over the microtiter plate well filled with working buffer solution N°1 such that the sensing electrode and reference electrode were immersed in the solution.

8.21. The custom software was started and used to record the sensing electrode potential in millivolts relative to the reference electrode potential over a period of 200 seconds.

8.22. On completion of 8.21, the holder was positioned over a microtiter plate well filled with working buffer solution N°2, in a manner similar to that described in 8.20.

- 81 -

8.23. The custom software was used to record the variation in millivolts of the sensing electrode potential relative to the reference electrode potential over a period of 600 seconds.

5

8.24. Using the custom software, the difference (δ) in millivolts between the background and final potential values was calculated.

10

8.25. The operations described in 8.20 - 8.24 were repeated in sequence using the samples containing DNA complementary to biotinylated DNA probe prepared at step 4.8.

15

8.26. The other half of the sensing electrodes with immobilised biotinylated single-strand DNA probe were removed from the microtubes containing initial buffer solution for DNA hybridisation and placed in the microtubes with samples containing DNA non-complementary to DNA probe, the microtubes containing the sensing electrode were then placed in a thermomixer and held for 120 minutes at +42°C, mixing continuously.

20

25

8.27. The procedures described in 8.19 - 8.25 were repeated using the samples containing DNA non-complementary to biotinylated DNA probe.

30

8.28. Based on the results obtained in 8.19 - 8.26, the custom software was used to plot statistical distribution curves of the δ values obtained with the samples of DNA complementary and non-complementary to biotinylated DNA probe.

35

Example 9.

5 Digoxin determination; competitive assay; samples-
samples with known digoxin concentration; receptor-
biotinylated mouse monoclonal antibodies to digoxin;
competing molecule-labelled digoxin; label-
peroxidase.

10 9.1 The procedures described in 1.1-1.4 were carried
out.

9.2 A solution was made up for electrochemical
polymerisation of pyrrole, as described in 2.2.

15 9.3 A polypyrrole film was formed by electrochemical
deposition, as described in 2.3.

20 9.4 The sensing electrode coated in polypyrrole film
was removed from the well, rinsed with deionised
water followed by 0.01M phosphate-saline buffer
solution (pH 7.4) and placed in a microtube with
300 μ l of storage solution, where it was stored at
+4°C.

25 9.5 To obtain the required number of sensing
electrodes, the procedures described in 9.1-9.4 were
repeated.

30 9.6 A solution of streptavidin was made up as
described in 2.6.

9.7 Streptavidin was bound on the surface of the
polypyrrole film covering the sensing electrode, as
described in 2.7.

35 9.8 A series of samples with known digoxin

- 83 -

concentration were prepared as follows:

250ml of ethanol were added to 750ml of
deionised water;

5

250mg of digoxin were dissolved in 1000ml of the
ethanol solution obtained;

10

a phosphate saline buffer tablet and 10.0g of
bovine serum albumin were dissolved in 200ml of
deionised water;

15

the digoxin solution obtained was sequentially
diluted in PBS solution with bovine serum
albumin at dilution rates of 250, 2500, 25000,
50000, 125000, 250000 and 500000 times;

20

200 μ l aliquots of each of the diluted samples
were placed in separate microtubes.

25

9.9 20 μ l of the purchased solution of biotin
conjugated mouse monoclonal antibodies to digoxin
were added to 19.98ml of 0.01M phosphate buffered
solution (pH 7.4), thoroughly mixed in a rotary
shaker, then aliquotted into microtubes in quantities
of 200 μ l.

30

9.10 Digoxin was conjugated with peroxidase
according to a previously described protocol, see
[21]. The resultant solution of peroxidase labelled
digoxin (final concentration ~0.1mg/ml) was diluted
with 0.01M phosphate saline buffer solution (pH 7.4)
at a dilution ratio of 10 times then divided into
aliquots of small volume (10 μ l) and stored at +4°C.

35

9.11 Working buffer solution N°1 was made up as described in 4.11.

5 9.12 Working buffer solution N°2 was made up as described in 4.12.

10 9.13 The sensing electrodes coated in polypyrrole film with bound streptavidin were removed from the storage buffer solution and each placed in a microtube containing the solution of biotin conjugated mouse monoclonal antibodies to digoxin (from step 9.9) and incubated for 10 minutes at room temperature.

15 9.14 Simultaneously with step 9.13, 2 μ l of the solution of peroxidase labelled digoxin (from step 9.10) was added to each of the samples with known digoxin concentration (from step 9.8), having first removed 2 μ l from the sample.

20 9.15 On completion of steps 9.13 and 9.14, the sensing electrodes were transferred to the tubes containing peroxidase labelled and unlabelled digoxin (from step 9.14); the tubes plus sensing electrodes
25 were then placed in a thermomixer and held for 10 minutes at 37 \pm 1°C, mixing continuously.

30 9.16 On completion of 9.15, the sensing electrodes were removed from the microtubes, rinsed for 3-5 seconds in 0.01M PBS and each placed in a microtiter plate well filled with working buffer solution N°1.

35 9.17 The sensing electrode and reference electrode were connected to the electrical contacts

- 85 -

of the holder connected to the PC-based measuring instrument, and the holder was positioned over the microtiter plate well filled with working buffer solution N°1 such that the sensing electrode and reference electrode were immersed in the working buffer.

9.18 The custom software was started and used to record the sensing electrode potential in millivolts relative to the reference electrode potential over a period of 30 seconds.

9.19 On completion of 9.18, the holder was positioned over a microtiter plate well filled with working buffer solution N°2, in a manner similar to that described in 9.17.

9.20 The custom software was used to record the variation in millivolts of the sensing electrode potential relative to the reference electrode potential over a period of 100 seconds.

9.21 Using the custom software, the area (integral) S_2 described by the curve of sensing electrode potential variation versus reference electrode potential was calculated.

9.22 The operations described in 9.17-9.21 were repeated in sequence using the samples with known digoxin concentration prepared at step 9.8.

9.23 Based on the results obtained at step 9.22, the custom software was used to plot the calibration curve " S_2 against digoxin concentration in the sample".

35

References

- 5
1. Kasparov S.V., Farmakovsky D.A., Kharlamov A.A.,
Damiryan A.U., Remen V.V. Device for detecting
biologically active compounds in biological
fluids and a method of manufacturing of the
10 sensing element. Patent of the Russian
Federation N°2032908.
 2. Kasparov S.V., Farmakovsky D.A. Electrochemical
immunoassay. WO 96/02001.
 - 15 3. Farmakovsky D.A., Milanovsky E. Yu., Cherkasov
V.R., Biryukov Yu. S., Komarov B.V. A method of
electrochemical indication of immuno-chemically
active macromolecules in test solutions. Patent
20 of the Russian Federation N°2107296.
 4. Ge Hailin, Wallace G.G. Ion exchange properties
of polypyrrole. Reactive polymers, 18, 133-140,
1992.
 - 25 5. Curtin L.S., Komplin G.C., Pietro W.J.,
Diffusive Anion Exchange in polypyrrole films.
J. of Physical Chemistry, 92, 12-13, 1988.
 - 30 6. Bobacks J., Gao Zh., Ivaska A., Lewenstam. A.,
Mechanism of ionic and redox sensitivity of p-
type conducting polymers. Part 2. Experimental
study of polypyrrole. J. of Electrochemical
35 Chemistry, 368, 33-41, 1994.

- 5 7. Scheller F., Pfeiffer D., Schubert F., Renneberg
 R., Kirstein D., Use of enzyme amperometric
 biosensors in the analysis of real subjects.
 Biosensors: Basic principles and attachments.
 Moscow.: Mir, 1992.
- 10 8. Taniguchi I., Yasukouchi K., Tsuji I.,
 Potential-causing element for immunosensor. EP
 0 193 154 A2.
- 15 9. Hodgson A.J., Spencer M.J., Wallace G.G.,
 Incorporation of proteins into conducting
 electroactive polymers. Reactive polymers 18,
 77-85, 1992.
- 20 10. John R., Spencer M.J., Wallace G.G., Smyth M.R..
 Development of a polypyrrole-based human serum
 albumin sensor. Antalytica Chimica Acta, 249,
 381-385, 1991.
- 25 11. Leary J.J., Brigati D.J., Ward D.C., Rapid and
 sensitive colorimetric method for visualising
 biotin-labelled DNA probes hybridised to DNA or
 RNA immobilised on nitrocellulose: bio-blots.
 Proc. Natl. Academy Science USA, 80, 4045-4049,
 1983.
- 30 12. Rosenstein R., Immuno-agglutination particle
 suspensions. EP 0 138 297 A1.
- 35 13. Schasfoort R.B.M., Bergveld P., Bomer J.,
 Kooyman R. P. H., Greve J., Modulation of the
 ISFET response by an immunological reaction.
 Sensors and Actuators, 17, 531-535, 1989.

14. Schasfoort R.B.M., Keldermans C.E.J.M., Kooyman R.P.H., Bergveld P., Greve J., Competitive immunological detection of progesterone by means of the ion-step induced response of an ImmunoFET. Sensors and Actuators B1, 368-372, 1990.
5
15. Schasfoort R.B.M., Kooyman R.P.H., Bergveld P., Greve J., A New Approach to ImmunoFET Operation. Biosensors and Bioelectronics, 5, 103-124, 1990.
10
16. Bergveld P., A critical evaluation of direct protein detection methods. Biosensors and Bioelectronics, 6, 55-72, 1991.
15
17. Hager H.J., Latex polymer reagents for diagnostic tests. United States Patent 3,857,931.
- 20 18. Spadaro A.M., Engler Ph. V., Lyophilisation of reagent-coated particles. EP 0 193 208 B1.
- 25 19. Harlow E., Lane D., Antibodies: A Laboratory Manual, Cold Spring Harbor, NY, 1988.
- 30 20. Rigby P.J.W., Dieckman M., Rhodes C., Berg R., Labelling deoxyribonucleic acid to high specific activity in vitro by nick-translation with DNA polymerase. J. of Molecular Biology, 113, 237-251, 1977.
21. Shan S. Wong, Chemistry of Protein Conjugation and Cross-Linking, CRC Press Inc, 1991.

Claims:

1. A sensing electrode for use in methods of electrochemical detection of an analyte, the sensing
5 electrode comprising an electrically conductive electrode coated with a layer of electroconductive polymer with adaptor molecules selected from the group consisting of avidin, streptavidin, anti-FITC antibodies and a molecule capable of specifically
10 binding to at least one class of receptor molecules immobilised therein or adsorbed thereto.
2. A sensing electrode as claimed in claim 1
15 in which the layer of electroconductive polymer has been doped with anions of large ionic radius.
3. A sensing electrode as claimed in claim 1
or claim 2 wherein the adaptor molecules are avidin or streptavidin and biotinylated receptors capable of
20 binding said analyte are attached thereto via a biotin/avidin or biotin/streptavidin binding interaction.
4. A sensing electrode as claimed in claim 1
25 or claim 2 wherein the adaptor molecules are protein A or protein G and antibodies capable of binding said analyte are attached thereto via a protein A/antibody or protein G/antibody binding interaction.
- 30 5. A sensing electrode as claimed in claim 1 or claim 2 wherein the adaptor molecules are lectins and receptors capable of binding said analyte are attached thereto via a lectin/carbohydrate binding interaction.

- 90 -

6. A sensing electrode as claimed in claim 1 or claim 2 wherein the adaptor molecules are anti-FITC antibodies and receptors capable of binding said analyte are attached thereto via a FITC/anti-FITC binding interaction.

7. An electrode assembly comprising a sensing electrode as claimed in any one of claims 1 to 6 and a reference electrode.

8. A method of producing a sensing electrode for use in methods of electrochemical detection of an analyte, the sensing electrode comprising an electrically conductive electrode coated with an electroconductive polymer with adaptor molecules selected from the group consisting of avidin, streptavidin, anti-FITC antibodies and a molecule capable of specifically binding to at least one class of receptor molecules immobilised therein, the method comprising the steps of:

a) preparing an electrochemical polymerisation solution comprising monomeric units of the electroconductive polymer and adaptor molecules,

b) immersing the electrode to be coated in the electrochemical polymerisation solution, and

c) applying a cyclic electric potential between the electrode and the electrochemical polymerisation solution to coat the electrode by electrochemical synthesis of the polymer from the solution, said cyclic electric potential being applied for at least one full cycle.

9. A method of producing a sensing electrode for use in methods of electrochemical detection of an analyte, the sensing electrode comprising an electrically conductive electrode coated with an electroconductive polymer with adaptor molecules selected from the group consisting of avidin, streptavidin, anti-FITC antibodies and a molecule capable of specifically binding to at least one class of receptor molecules adsorbed thereto, the method comprising steps of:

a) preparing an electrochemical polymerisation solution comprising monomeric units of the electroconductive polymer,

b) immersing the electrode to be coated in the electrochemical polymerisation solution,

c) applying a cyclic electric potential between the electrode and the electrochemical polymerisation solution to coat the electrode by electrochemical synthesis of the polymer from the solution, said cyclic electric potential being applied for at least one full cycle; and

d) contacting the coated electrode with a solution comprising adaptor molecules such that the adaptor molecules are adsorbed onto the electroconductive polymer coating of the electrode.

10. A method as claimed in claim 8 or claim 9 wherein the adaptor molecules are avidin or streptavidin and the method further comprises the step of contacting the sensing electrode with a solution comprising receptor molecules, said receptor

- 92 -

molecules being conjugated with biotin such that said biotinylated receptors bind to molecules of avidin or streptavidin immobilised in or adsorbed to the electroconductive polymer coating of the electrode
5 via a biotin/avidin or biotin/streptavidin binding interaction.

11. A method as claimed in claim 10 wherein the receptor molecules are monoclonal antibodies,
10 polyclonal antibodies, antibody fragments, antibody mimics, chimaeric antibodies viral lysates, recombinant proteins, synthetic peptides, hormones, hormone receptors, single stranded nucleic acids, low molecular weight molecules, chemical compounds
15 conjugated with proteins (haptens), fragments of bacterial, plant or animal cells, lectins, glycoproteins or carbohydrates.

12. A method as claimed in claim 8 or claim 9
20 wherein the adaptor molecules are protein A, protein G or lectins.

13. A method as claimed in any one of claims 8 to 12 wherein the cyclic electric potential has a
25 sawtooth form.

14. A method as claimed in any one of claims 8 to 13 wherein the cyclic electric potential is applied for at least two cycles.
30

15. A method as claimed in any one of claims 8 to 14 wherein the cyclic electric potential has a peak value applied to the electrode which is less than or equal to +2 volts.
35

16. A method as claimed in any one of claims 8 to 13 in which a salt whose anions have a large ionic radius is added to the electrochemical polymerisation solution.

5

17. A method as claimed in claim 16 wherein the salt is sodium dodecylsulphate or sodium dextran sulphate.

10

18. A method as claimed in any one of claims 8 to 17 wherein the monomeric units of the electroconductive polymer are aniline, thiophene, furan or pyrrole.

15

19. A method of electrochemical detection of an analyte in a sample, which method comprises the steps of:

a) providing a sensing electrode having an electroconductive polymer coating, the coating having immobilised therein or adsorbed thereto receptors which are capable of binding the desired analyte to be detected in the sample;

20

b) contacting the sensing electrode with a test solution comprising the sample so that said desired analyte binds to said immobilised or adsorbed receptors;

25

c) contacting the sensing electrode with a solution comprising secondary receptors capable of binding to said analyte at a site spatially distinct from the site of binding to the immobilised or adsorbed receptors, said secondary receptors being conjugated with a charge label;

30

35

- 94 -

d) monitoring the electric potential difference between the treated sensing electrode and a reference electrode when both are immersed in an electrolyte; and

5

e) monitoring the electric potential difference between the sensing electrode and a reference electrode following a change in the ionic strength of the electrolyte at constant pH.

10

20. A method of electrochemical detection of an analyte in a sample, which method comprises the steps of:

a) providing a sensing electrode having an electroconductive polymer coating, the coating having immobilised therein or adsorbed thereto receptors which are capable of binding to the desired analyte to be detected in the sample;

b) contacting the sensing electrode with a test solution comprising the sample so that said analyte binds to said immobilised or adsorbed receptors;

c) contacting the sensing electrode with a solution comprising competing molecules capable of binding to said immobilised or adsorbed receptors, said competing molecules being conjugated with a charge label;

30

d) monitoring the electric potential difference between the treated sensing electrode and a reference electrode when both are immersed in an electrolyte; and

35

- 95 -

e) monitoring the electric potential difference between the sensing electrode and a reference electrode following a change in the ionic strength of the electrolyte at constant pH.

5

21. A method as claimed in claim 19 or claim 20 wherein the charge label has the following properties:

10 (i) it carries a net charge at the pH of the electrolyte of part d); and

(ii) the magnitude of this charge changes in response to a change in the ionic strength of the electrolyte at constant pH;

15 22. A method as claimed in claim 21 wherein the charge label is ferrocene, latex microspheres or gold.

20 23. A method as claimed in any one of claims 19 to 22 wherein steps (b) and (c) are performed simultaneously by contacting the sensing electrode with a test solution to which has been added secondary receptors or competing molecules conjugated with a charge label.

25

24. A method of electrochemical detection of an analyte in a sample, which method comprises the steps of:

30 (a) providing a sensing electrode having an electroconductive polymer coating, the coating having immobilized therein or adsorbed thereto receptors which are capable of binding to the desired analyte to be detected in the sample;

35 (b) contacting the sensing electrode with a

- 96 -

test solution comprising the sample so that the said analyte binds to said immobilized or adsorbed receptors;

5 (c) contacting the sensing electrode with a solution comprising secondary receptors capable of binding to said analyte at a site spatially distinct from the site of binding to immobilized or adsorbed receptors, said secondary receptors being conjugated
10 with an enzyme;

 d) monitoring the electric potential difference between the treated sensing electrode and a reference electrode when both are immersed in an
15 electrolyte; and

 e) monitoring the electric potential difference between the sensing electrode and a reference electrode following exposure to an
20 electrolyte comprising the substrate for said enzyme.

25. A method of electrochemical detection of an analyte in a sample, which method comprises the steps of:

25 (a) providing a sensing electrode having an electroconductive polymer coating, the coating having immobilized therein or adsorbed thereto receptors which are capable of binding to the desired analyte to be detected in the sample;

30

 (b) contacting the sensing electrode with a test solution comprising the sample so that the said desired analyte binds to said immobilized or adsorbed receptors;

35

- 97 -

(c) contacting the sensing electrode with a solution comprising competing molecules capable of binding to said immobilized or adsorbed receptors, said competing molecules being conjugated with an enzyme;

(d) monitoring the electric potential difference between the treated sensing electrode and a reference electrode when both are immersed in an electrolyte; and

(e) monitoring the electric potential difference between the sensing electrode and a reference electrode following exposure to an electrolyte comprising the substrate for said enzyme.

26. A method as claimed in claim 24 or claim 25 wherein the enzyme is capable of converting a substrate which directly affects the redox composition of the electroconductive polymer coating of the sensing electrode to a product which has no detectable effect on the redox composition of the said electroconductive polymer coating.

27. A method as claimed in claim 26 wherein the enzyme is a peroxidase.

28. A method as claimed in claim 24 or claim 25 wherein the enzyme is capable of converting a substrate which has no detectable effect on the redox composition of the electroconductive polymer coating of the sensing electrode to a product capable of directly or indirectly affecting the redox composition of the said electroconductive polymer coating.

- 98 -

29. A method as claimed in claim 28 wherein the product capable of indirectly affecting the redox composition of the electroconductive polymer membrane causes a change in the pH of the electrolyte of part (e).

30. A method as claimed in claim 29 wherein the enzyme is a urease.

31. A method as claimed in claim 24 or claim 25 wherein the enzyme is capable of converting a substrate which has no detectable effect on the redox composition of the electroconductive polymer coating of the sensing electrode to a product which is a substrate for a second enzyme, the action of the second enzyme generating a second product which directly or indirectly affects the redox composition of the electroconductive polymer coating of the sensing electrode.

32. A method as claimed in any one of claims 24 to 31 wherein steps (b) and (c) are performed simultaneously by contacting the sensing electrode with a test solution to which has been added secondary receptors or competing molecules conjugated with an enzyme label.

33. A method as claimed in any one of claims 19 to 32 wherein the receptors capable of binding to the analyte to be detected are biotinylated and are attached to avidin or streptavidin immobilised in or adsorbed to the electroconductive polymer coating of the sensing electrode via a biotin/avidin or biotin/streptavidin binding interaction.

- 99 -

34. A method as claimed in any one of claims 19 to 32 wherein the receptors capable of binding to the analyte to be detected are antibodies and are attached to protein A or protein G immobilized in or adsorbed to the electroconductive polymer coating of the sensing electrode via a protein A/antibody or protein G/antibody binding interaction.

35. A method as claimed in any one of claims 19 to 32 wherein the receptors capable of binding to the analyte to be detected contain a sugar moiety and are attached to lectins immobilized in or adsorbed to the electroconductive polymer coating of the sensing electrode via a lectin/sugar binding interaction.

36. A method as claimed in any one of claims 19 to 32 wherein the receptors capable of binding to the analyte to be detected are labelled with FITC and are attached to anti-FITC antibodies immobilized in or adsorbed to the electroconductive polymer coating of the sensing electrode via a FITC/anti-FITC binding interaction.

37. A method as claimed in any one of claims 19 to 36 wherein the sensing electrode is produced according to the method of any one of claims 8 to 18.

38. A method as claimed in claim 33 wherein steps (b) and (c) are performed simultaneously with a step of contacting the sensing electrode with biotinylated receptors by contacting the sensing electrode with a test solution to which has been added biotinylated receptors and secondary receptors or competing molecules conjugated with a charge label or an enzyme.

- 100 -

39. A method as claimed in claim 19 wherein the secondary receptors are polyclonal antibodies or monoclonal antibodies.

5 40. A method as claimed in any one of claims 19 to 39 in which biological fluids such as whole blood, serum, lymph, urine, saliva, cerebrospinal fluid and semen are used as the test solution.

10 41. A method of electrochemical detection of an analyte in a sample, which method comprises the steps of:

 (a) providing a sensing electrode comprising an electrically conductive electrode coated with a layer of electroconductive polymer with molecules of avidin or streptavidin immobilized therein or adsorbed thereto, said avidin or streptavidin molecules being attached to receptor molecule capable of binding the analyte to be detected attached via a biotin/avidin or biotin/streptavidin binding interaction;

15
20

 (b) contacting the sensing electrode with a test solution comprising the sample so that said desired analyte binds to said immobilized or adsorbed receptor molecules;

25

 (c) monitoring the potential of the sensing electrode relative to a reference electrode when both are immersed in an electrolyte; and

30

 (d) monitoring the potential difference of the sensing electrode relative to the reference electrode following a change in the ionic strength or composition of the electrolyte at constant pH.

35

- 101 -

42. A method as claimed in claim 41 wherein the analyte to be detected is a nucleic acid and the receptor molecules are oligonucleotides.




Fig.1




Fig.2




Fig.3




Fig.4




Fig. 5




Fig. 6







Fig. 7



A



B



C

Fig.8




Fig.9




Fig.10




Fig.11

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 99/02785

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G01N33/543 G01N27/327 C12Q1/28 C12Q1/58 C12Q1/68

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GUISEPPI-ELIE, A. ET AL: "Electroconductive polymer thin films with internal bioactive moieties for biosensor applications" POLYM. MATER. SCI. ENG. (1995), 72, 404-5 , XP000853822 the whole document	1,8,9, 19,20, 24,25,41
A	WO 98 35232 A (NOVALON PHARMACEUTICAL CORP ;UNIV NORTH CAROLINA (US); FOWLKES DAN) 13 August 1998 (1998-08-13) examples	1,8,9, 19,20, 24,25,41
A	US 5 312 762 A (GUISEPPI-ELIE ANTHONY) 17 May 1994 (1994-05-17) abstract	1,8,9, 19,20, 24,25,41



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

25 November 1999

Date of mailing of the international search report

03/12/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 851 epo nl,
Fax (+31-70) 340-3018

Authorized officer

Moreno, C

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 99/02785

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 89 11649 A (WOLLONGONG UNIADVICE) 30 November 1989 (1989-11-30) cited in the application the whole document	1,8,9, 19,20, 24,25,41
A	EP 0 193 154 A (CHEMO SERO THERAPEUT RES INST) 3 September 1986 (1986-09-03) cited in the application the whole document	1,8,9, 19,20, 24,25,41

INTERNATIONAL SEARCH REPORT

Information on patent family members

In. rnational Application No

PCT/GB 99/02785

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9835232 A	13-08-1998	AU 6651798 A NO 993764 A	26-08-1998 28-09-1999
US 5312762 A	17-05-1994	WO 9306237 A CA 2048692 A WO 9010655 A US 5766934 A US 5352574 A	01-04-1993 14-09-1990 20-09-1990 16-06-1998 04-10-1994
WO 8911649 A	30-11-1989	NONE	
EP 0193154 A	03-09-1986	JP 1961890 C JP 6097219 B JP 61195346 A AT 72333 T CA 1241057 A DE 3683656 A	25-08-1995 30-11-1994 29-08-1986 15-02-1992 23-08-1988 12-03-1992